


Soft Recovery Ultrafast Plastic Rectifier

Reverse Voltage 50 to 200V
Forward Current 3.5A



DO-201AD



Dimensions in inches and (millimeters)

Features

- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- Ideally suited for use in very high frequency switching power supplies, inverters and as free wheeling diodes
- Ultrafast recovery time for high efficiency
- Glass passivated junction
- High temperature soldering guaranteed:
250°C/10 seconds, 0.375" (9.5mm) lead length,
5 lbs. (2.3kg) tension

Mechanical Data

Case: JEDEC DO-201AD molded plastic body over passivated chip

Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.045 oz., 1.2 g

Maximum Ratings & Thermal Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbols	SBYV28-50	SBYV28-100	SBYV28-150	SBYV28-200	Units
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	V
Maximum RMS voltage	V _{RMS}	35	70	105	140	V
Maximum DC blocking voltage	V _{DC}	50	100	150	200	V
Minimum reverse breakdown voltage at 100μA	V _(BR)	55	110	165	220	V
Maximum average forward rectified current 0.375" (9.5mm) lead lengths at T _L = 85°C	I _{F(AV)}	3.5				A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load at T _J = 150°C	I _{FSM}	90				A
Typical thermal resistance ⁽¹⁾	R _{θJA}	25				°C/W
Operating and storage temperature range	T _J , T _{STG}	-55 to +150				°C

Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbols	SBYV28-50	SBYV28-100	SBYV28-150	SBYV28-200	Units
Maximum instantaneous forward voltage at 3.5A ⁽²⁾	V _F T _J =25°C T _J =150°C	1.1 0.89				V
Maximum DC reverse current at rated DC blocking voltage	I _R T _A =25°C T _A =100°C	5.0 300				μA
Maximum reverse recovery time at I _F = 0.5A, I _R = 1.0A, I _{rr} = 0.25A	t _{rr} T _J =25°C	20				ns
Typical junction capacitance at 4.0V, 1MHz	C _J	20				pF

Notes:

(1) Lead length = 3/8" on P.C. Board with 1.5" x 1.5" copper surface

(2) Pulse test: t_p = 300μs, duty cycle ≤ 2%

SBYV28-50 thru SBYV28-200



Vishay Semiconductors
formerly General Semiconductor

Ratings and Characteristic Curves ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig. 1 – Forward Current Derating Curves




Fig. 2 – Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 – Typical Instantaneous Forward Characteristics




Fig. 4 – Typical Reverse Leakage Characteristics




Fig. 5 – Reverse Switching Characteristics




Fig. 6 – Typical Junction Capacitance

