LNA2601L

GaAs Infrared Light Emitting Diode

For optical control systems



Features

- High-power output, high-efficiency
- Emitted light spectrum suited for silicon photodetectors
- Infrared light emission close to monochromatic light : λ_P = 950 nm
- Ultra-miniature, thin side-view type package

Absolute Maximum Ratings (Ta = 25˚C)

Parameter	Symbol	Ratings	Unit
Power dissipation	P_D	75	mW
Forward current (DC)	I_F	50	mA
Pulse forward current	I_{FP}*	1	A
Reverse voltage (DC)	V_R	3	V
Operating ambient temperature	T_{opr}	–25 to +85	˚C
Storage temperature	T_{stg}	– 40 to +100	˚C

* f = 100 Hz, Duty cycle = 0.1 %

Electro-Optical Characteristics (Ta = 25˚C)

Parameter	Symbol	Conditions	min	typ	max	Unit
Radiant power	P_O	I_F = 50mA	1.5			mW
Peak emission wavelength	λ_P	I_F = 50mA		950		nm
Spectral half band width	$\Delta\lambda$	I_F = 50mA		50		nm
Forward voltage (DC)	V_F	I_F = 50mA			1.5	V
Reverse current (DC)	I_R	V_R = 3V			10	µA
Capacitance between pins	C_t	V_R = 0V, f = 1MHz		35		pF
Half-power angle	θ	The angle in which radiant intencity is 50%		20		deg.

I_F — Ta



I_{FP} — Duty cycle



I_F — V_F



ΔP_O — I_{FP}



V_F — Ta



ΔP_O — Ta



λ_P — Ta



Spectral characteristics



Directivity characteristics