

# SIEMENS

# NEW

## IL350T/351T/358T/359T HIGH PERFORMANCE LINEAR OPTOCOUPLER for Optical DAA in Telecommunications

Preliminary Data Sheet

### FEATURES


- 2 mm High SMT Package
- High Sensitivity (K1) at Low Operating LED Current
- Couples AC and DC Signals
- Low Input-Output Capacitance
- Isolation Voltage, 2500 V<sub>RMS</sub>
- Low Distortion
- Available in Tape and Reel (suffix T)

### APPLICATIONS

- Optical DAA for V.34 FAX/Modem PCMCIA Cards
- Digital Telephone Line Isolation

### DESCRIPTION

The IL350T/1T/8T/9T family of Linear Optocoupler consist of an IRLED optically coupled to two photodiodes. The emitter mechanical faces both diodes enabling them to receive approximately an equal amount of infrared light. The diodes produce a proportionate amount of photocurrents. The ratio of photocurrents stays constant with high accuracy when either the LED current changes or ambient temperature changes. Thus one can control the output diode current optically controlling the input photodiode current. The IL350T/1T/8T/9T optocouplers can be used with the aid of operational amplifiers in closed loop conditions to achieve high and electrically isolated AC and or DC amplifiers.



### Absolute Maximum Ratings

Emitter	Sym	Min.	Max.	Units
Reverse Voltage	R V		3	V
Forward Current	F I		30	mA
Surge Current	F <sub>K</sub>		150	mA
Pulse Width μs				
Power Dissipation @ 25°C	P <sub>LED</sub>		150	mW
Derate Linearly from 25			2	mW/°C
Junction Temperature	J T		100	°C
<b>Detector (each)</b>				
Reverse Voltage	R V		15	V
Power Dissipation	P		50	mW
Derate Linearly from 25			0.65	mW/°C
Junction Temperature	J T		100	°C
<b>Coupler</b>				
Isolation Test Voltage	ISOL V	2500		RMS
Total Package Power Dissipation	Pt		250	mW
Derate Linearly from 25			2.8	mW/°C
Storage Temperature	S T	- 40	150	°C
Operating Temperature	OP T	0	75	°C
Lead Soldering Time @ 260			10	sec.
Isolation Resistance				
V <sub>IO</sub> =500 V, T <sub>A</sub> =25		10 <sup>12</sup> Ω		
V <sub>IO</sub> =500 V, T <sub>A</sub> =100		10 <sup>11</sup> Ω		

**Electrical Characteristics (T<sub>A</sub>=25°C)**

LED Emitter		Symbol	Min.	Typ.	Max.	Units	Test Conditions
Forward Voltage		V <sub>F</sub>		1.8	2.1	V	I <sub>F</sub> =10 mA
Reverse Current		I <sub>R</sub>		.01	10	μA	V <sub>R</sub> =3 V
V <sub>F</sub> Temperature Coefficient		ΔV <sub>F</sub> /ΔT		-2.2		mV/°C	
Junction Capacitance		C <sub>J</sub>		TBD		pF	V <sub>F</sub> =0 V, f=1 MHz
Dynamic Resistance		r <sub>d</sub>		6		Ω	
Switching Time IL358T/9T		t <sub>F</sub>		40		ns	I <sub>F</sub> =2.5 mA ΔI <sub>F</sub> =1 mA
		t <sub>R</sub>		40		ns	
<b>Detector</b>							
Junction Capacitance		C <sub>J</sub>		12		pF	V <sub>F</sub> =0 V, f=1 MHz
NEP				<4 <sup>-14</sup>		W/√Hz	V <sub>DET</sub> =0 V
<b>AC Characteristics Photovoltaic Mode</b>							
Frequency Response	IL358T/9T	FBW (-3dB)		1.0		MHz	I <sub>F</sub> =25 μA Modulation current ΔI <sub>F</sub> ±6 μA
Phase Response				45		Deg.	
Rise Time				350		ns	
<b>Package</b>							
Input-Output Capacitance		C <sub>IO</sub>		1		pF	V <sub>F</sub> =0 V, f=1 MHz
Common Mode Capacitance		C <sub>cm</sub>		0.5		pF	V <sub>F</sub> =0 V, f=1 MHz
<b>Coupled Characteristics</b>							
				<b>K1 at I<sub>F</sub>=2 mA, V<sub>D</sub>=0 V</b>			<b>K3 Bins</b>
				<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	
IL350T				0.003			A-J
IL351T				0.005			D, E, F, G
IL358T				0.008			D, E, F, G
IL359T				0.008			E, F

**Bin Table**

Bin	Min.	Max.
A	0.557	0.626
B	0.620	0.696
C	0.690	0.773
D	0.765	0.859
E	0.851	0.955
F	0.945	1.061
G	1.051	1.181
H	1.169	1.311
I	1.297	1.456
J	1.442	1.618