

PHASE CONTROL THYRISTORS

Stud Version

Features

- High current and high surge ratings
- $dv/dt = 1000V/\mu s$ option
- Glass-metal seal up to 1200V
- Threaded studs UNF 1/2"-20UNF-2A
- Types up to 1200V V_{RRM}/V_{DRM}
- $di/dt = 300A/\mu s$


110A

Typical Applications

- DC motor controls
- Controlled DC power supplies
- AC controllers

Major Ratings and Characteristics

Parameters	111RIA	Units
$I_{T(AV)}$	110	A
@ T_C	90	°C
$I_{T(RMS)}$	172	A
I_{TSM} @ 50Hz	2080	A
@ 60Hz	2180	A
I^2t @ 50Hz	21.7	KA ² s
@ 60Hz	19.8	KA ² s
V_{DRM}/V_{RRM}	400 to 1200	V
t_q typical	110	μs
T_J	- 40 to 140	°C



111RIA Series

Bulletin I25204 01/01

International
IRF Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code	V_{DRM}/V_{RRM} max. repetitive peak and off-state voltage V	V_{RSM} maximum non-repetitive peak voltage V	I_{DRM}/I_{RRM} max. @ $T_J = T_J$ max. mA
111RIA	40	400	500	20
	80	800	900	
	120	1200	1300	

On-state Conduction

Parameter	111RIA	Units	Conditions	
$I_{T(AV)}$ Max. average on-state current @ Case temperature	110	A	180° conduction, half sine wave	
	90	°C		
$I_{T(RMS)}$ Max. RMS on-state current	172	A	DC @ 83°C case temperature	
I_{TSM} Max. peak, one-cycle non-repetitive surge current	2080		t = 10ms	No voltage reappplied
	2180		t = 8.3ms	reappplied
	1750		t = 10ms	100% V_{RRM} reappplied
I^2t Maximum I^2t for fusing	1830	t = 8.3ms	reappplied	
	21.7	t = 10ms	No voltage reappplied	
		t = 8.3ms	reappplied	
	19.8	t = 10ms	100% V_{RRM} reappplied	
15.3	t = 8.3ms	reappplied		
14.0				
$I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing	217	$KA^2\sqrt{s}$	t = 0.1 to 10ms, no voltage reappplied	
$V_{T(TO)1}$ Low level value of threshold voltage	0.82	V	$(16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)})$, $T_J = T_J$ max.	
$V_{T(TO)2}$ High level value of threshold voltage	1.02		$(I > \pi \times I_{T(AV)})$, $T_J = T_J$ max.	
r_{t1} Low level value of on-state slope resistance	2.16	mΩ	$(16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)})$, $T_J = T_J$ max.	
r_{t2} High level value of on-state slope resistance	1.70		$(I > \pi \times I_{T(AV)})$, $T_J = T_J$ max.	
V_{TM} Max. on-state voltage	1.57	V	$I_{pk} = 350A$, $T_J = T_J$ max., $t_p = 10ms$ sine pulse	
I_H Maximum holding current	150	mA	$T_J = 25^\circ C$, anode supply 6V resistive load	
I_L Typical latching current	400			

Switching

Parameter	111RIA	Units	Conditions
di/dt Max. non-repetitive rate of rise of turned-on current	300	A/μs	Gate drive 20V, 20Ω, $t_r \leq 1\mu s$ $T_J = T_J$ max, anode voltage $\leq 80\% V_{DRM}$
t_d Typical delay time	1	μs	Gate current 1A, $di_g/dt = 1A/\mu s$ $V_d = 0.67\% V_{DRM}$, $T_J = 25^\circ C$
t_q Typical turn-off time	110		$I_{TM} = 50A$, $T_J = T_J$ max., $di/dt = -5A/\mu s$, $V_R = 50V$ $dv/dt = 20V/\mu s$, Gate 0V 25Ω

Blocking

Parameter	111RIA	Units	Conditions
dv/dt Maximum critical rate of rise of off-state voltage	500	V/ μ s	$T_J = T_J$ max. linear to 80% rated V_{DRM}
I_{RRM} I_{DRM} Max. peak reverse and off-state leakage current	20	mA	$T_J = T_J$ max, rated V_{DRM}/V_{RRM} applied

Triggering

Parameter	111RIA	Units	Conditions
P_{GM} Maximum peak gate power	12	W	$T_J = T_J$ max, $t_p \leq 5$ ms
$P_{G(AV)}$ Maximum average gate power	3.0		$T_J = T_J$ max, $f = 50$ Hz, $d\% = 50$
I_{GM} Max. peak positive gate current	3.0	A	$T_J = T_J$ max, $t_p \leq 5$ ms
$+V_{GM}$ Maximum peak positive gate voltage	20	V	$T_J = T_J$ max, $t_p \leq 5$ ms
$-V_{GM}$ Maximum peak negative gate voltage	10		
I_{GT} DC gate current required to trigger	TYP.	MAX.	$T_J = -40^\circ\text{C}$ $T_J = 25^\circ\text{C}$ $T_J = 140^\circ\text{C}$ Max. required gate trigger/ current/ voltage are the lowest value which will trigger all units 12V anode-to-cathode applied
	180	-	
	80	120	
V_{GT} DC gate voltage required to trigger	2.5	-	$T_J = -40^\circ\text{C}$ $T_J = 25^\circ\text{C}$ $T_J = 140^\circ\text{C}$
	1.6	2	
	1	-	
I_{GD} DC gate current not to trigger	6.0	mA	$T_J = T_J$ max Max. gate current/ voltage not to trigger is the max. value which will not trigger any unit with rated V_{DRM} anode-to-cathode applied
V_{GD} DC gate voltage not to trigger	0.25	V	

Thermal and Mechanical Specification

Parameter	111RIA	Units	Conditions
T_J Max. operating temperature range	-40 to 140	$^\circ\text{C}$	
T_{stg} Max. storage temperature range	-40 to 150		
R_{thJC} Max. thermal resistance, junction to case	0.27	K/W	DC operation
R_{thCS} Max. thermal resistance, case to heatsink	0.1		Mounting surface, smooth, flat and greased
T Mounting torque, $\pm 10\%$	15.5	Nm (lbf-in)	Non lubricated threads
	(137)		Lubricated threads
	14 (120)		
wt Approximate weight	130	g	
Case style	TO-209AC (TO-94)		See Outline Table

111RIA Series

Bulletin I25204 01/01

ΔR_{thJC} Conduction

(The following table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction	Rectangular conduction	Units	Conditions
180°	0.043	0.031	K/W	$T_J = T_J \text{ max.}$
120°	0.052	0.053		
90°	0.066	0.071		
60°	0.096	0.101		
30°	0.167	0.169		

Ordering Information Table

Device Code

11	1	RIA	120
----	---	-----	-----

1
2
3
4
5

- 1** - $I_{T(AV)}$ rated average output current (rounded/10)
- 2** - 0 = Eyelet terminals (Gate and Auxiliary Cathode Leads)
1 = Fast - on terminals (Gate and Auxiliary Cathode Leads)
2 = Flag terminals (For Cathode and Gate Terminals)
- 3** - Thyristor
- 4** - Voltage code: Code x 10 = V_{RRM} (See Voltage Rating Table)
- 5** - Critical dv/dt: None = 500V/ μ sec
S90 = 1000V/ μ sec

Outline Table

GLASS-METAL SEAL
FLAG TERMINALS

23.5 DIA.
 (0.93) MAX.
 1.5 (0.06) DIA.
 12 (0.47)
 24 (0.94) MAX.
 10 (0.39) MAX.
 2 (0.83) MAX.
 1/2"-20UNF-2A*
 SW 27
 16.5 (0.65)
 2.4 (0.09)
 29.5 (1.16)

5.5 (0.22) DIA.
 10 (0.39)
 5.6 (0.22)

Case Style TO-208AD (TO-83)
All dimensions in millimeters (inches)

* FOR METRIC DEVICE: M12 x 1.75 E 6

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 4 - On-state Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristic




Fig. 9 - Gate Characteristics

111RIA Series

Bulletin I25204 01/01

International
IOR Rectifier

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 01/01