

NTE3061 thru NTE3064 0.3" Single Digit Numeric Display, Seven Segment, Common Anode

Description:

The NTE3061 through NTE3064 are 0.3 inch (7.62mm) height single digit, seven segment, common anode displays. The NTE3061 utilizes LED chips which are made from GaAsP on a GaAs substrate. The NTE3063 utilizes LED chips which are made from GaP on a transparent GaP substrate. The NTE3062 and NTE3064 utilize LED chips which are made from GaAsP on a transparent GaP substrate.

Features:

- 0.3 Inch (7.62mm) Digit Height
- Choice of Four Bright Colors:
 - Red – NTE3061
 - Orange – NTE3062
 - Green – NTE3063
 - Yellow – NTE3064
- Low Power Requirement
- Excellent Characters Appearance
- Categorized for Luminous Intensity
- IC Compatible
- Easy Mounting on PC Board or Sockets

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Power Dissipation (Per Segment), P_T	
NTE3061	55mW
NTE3062, NTE3063	75mW
NTE3064	60mW
Peak Forward Current (Per Segment, 1/10 Duty Cycle, 0.1ms Pulse Width), I_{Fpeak}	
NTE3061	160mA
NTE3062, NTE3063	100mA
NTE3064	80mA
Continuous Forward Current (Per Segment), I_F	
NTE3061, NTE3062, NTE3063	25mA
NTE3064	20mA
Derate Linearly from 25°C (Per Segment)	
NTE3061, NTE3062, NTE3063	0.30mA/°C
NTE3064	0.24mA/°C
Reverse Voltage (Per Segment), V_R	5V
Operating Temperature Range, T_{opr}	-25° to +85°C
Storage Temperature Range, T_{stg}	-25° to +85°C
Lead Temperature (During Solder, 1/16" Below Seating Plane, 3sec max), T_L	+260°C

Electrical/Optical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Average Luminous Intensity NTE3061	I_V	$I_F = 10\text{mA}$	200	500	–	μcd
NTE3062, NTE3063, NTE3064			800	2000	–	μcd
Peak Emission Wavelength NTE3061	λ_P	$I_F = 20\text{mA}$	–	655	–	nm
NTE3062			–	630	–	nm
NTE3063			–	565	–	nm
NTE3064			–	585	–	nm
Spectral Line Half-Width NTE3061	$\Delta\lambda$	$I_F = 20\text{mA}$	–	24	–	nm
NTE3062			–	40	–	nm
NTE3063			–	30	–	nm
NTE3064			–	35	–	nm
Forward Voltage, Any Segment or D.P. NTE3061	V_F	$I_F = 20\text{mA}$	–	1.7	2.0	V
NTE3062, NTE3063, NTE3064			–	2.1	2.8	V
Reverse Current, Any Segment or D.P.	I_R	$V_R = 5\text{V}$	–	–	100	μA
Luminous Intensity Matching Ratio	I_{V-m}	$I_F = 20\text{mA}$	–	–	2:1	

Pin Connection Diagram



