


DETAIL A:



| | | | | | | | | | | | | | | | | | | | | | |
|----|-----------------|-----------------|----------------|----|----|----|-----|----|-------|-----|-----|-----|-----|-----|-----|-----|-----|----|----|------|------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 |
| FG | V _{SS} | V _{CC} | V _O | WR | RD | CE | C/D | NC | RESET | DB0 | DB1 | DB2 | DB3 | DB4 | DB5 | DB6 | DB7 | FS | NC | LED+ | LED- |

NOTES:

1. DISPLAY TYPE: STN/YELLOW-GREEN MODE
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
4. OPERATING TEMP.: 0°C+50°C
5. STORAGE TEMP.: -20°C+60°C
6. CONTROLLER: T6963C
7. LCD OPERATING VOLTAGE: 14.3V
8. LCD DRIVE METHOD: DUTY 1/64 BIAS 1/9
9. ALL UNMARKED TOLERANCES: ±0.3mm
10. BACKLIGHT TYPE: LED
11. BEZEL IS TO BE PAINTED BLACK



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

| | | |
|---------------|-------------------------|----------|
| DRAWN BY: | TITLE: TM24064LBC | |
| CHECKED BY: | DWG NO: G-1 | |
| APPROVED BY: | DWG NAME: TM24064LBCG-1 | UNIT: mm |
| CONFIRMED BY: | SHEET NO: 0F | |