


Switchmode Full Plastic Dual Ultrafast Power Rectifiers

... Designed for use in switching power supplies, inverters and as free wheeling diodes. These state-of-the-art devices have the following features:

- * High Surge Capacity
- * Low Power Loss, High efficiency
- * Glass Passivated chip junctions
- * 150 °C Operating Junction Temperature
- * Low Stored Charge Majority Carrier Conduction
- * Low Forward Voltage, High Current Capability
- * High-Switching Speed 35 Nanosecond Recovery Time
- * Plastic Material used Carries Underwriters Laboratory

**ULTRA FAST
RECTIFIERS**


**20 AMPERES
50 – 200 VOLTS**



ITO-220

MAXIMUM RATINGS

| Characteristic | Symbol | URF20 | | | | Unit |
|--------------------------------------------------------------------------------------------------------------|---------------------------------|---------------|-----|-----|-----|------|
| | | 05 | 10 | 15 | 20 | |
| Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage | V_{RRM} V_{RWM} V_R | 50 | 100 | 150 | 200 | V |
| RMS Reverse Voltage | $V_{R(RMS)}$ | 35 | 70 | 105 | 140 | V |
| Average Rectifier Forward Current Per Leg Per Total Device $T_C=125^\circ\text{C}$ | $I_{F(AV)}$ | 10 20 | | | | A |
| Peak Repetitive Forward Current (Rate V_R , Square Wave, 20kHz, $T_C=125^\circ\text{C}$) | I_{FM} | 20 | | | | A |
| Non-Repetitive Peak Surge Current (Surge applied at rate load conditions halfwave, single phase, 60Hz) | I_{FSM} | 150 | | | | A |
| Operating and Storage Junction Temperature Range | T_J, T_{stg} | - 65 to + 150 | | | | °C |



| DIM | MILLIMETERS | |
|-----|-------------|-------|
| | MIN | MAX |
| A | 15.05 | 15.15 |
| B | 13.35 | 13.45 |
| C | 10.00 | 10.10 |
| D | 6.55 | 6.65 |
| E | 2.65 | 2.75 |
| F | 1.55 | 1.65 |
| G | 1.15 | 1.25 |
| H | 0.55 | 0.65 |
| I | 2.50 | 2.60 |
| J | 3.00 | 3.20 |
| K | 1.10 | 1.20 |
| L | 0.55 | 0.65 |
| M | 4.40 | 4.60 |
| N | 1.15 | 1.25 |
| P | 2.65 | 2.75 |
| O | 3.35 | 3.45 |
| Q | 3.15 | 3.25 |

ELECTRICAL CHARACTERISTICS

| Characteristic | Symbol | URF20 | | | | Unit |
|--------------------------------------------------------------------------------------------------------------------------------------|----------|----------------|----|----|----|------|
| | | 05 | 10 | 15 | 20 | |
| Maximum Instantaneous Forward Voltage ($I_F=10$ Amp, $T_C=25^\circ\text{C}$) ($I_F=10$ Amp, $T_C=125^\circ\text{C}$) | V_F | 0.975 0.880 | | | | V |
| Maximum Instantaneous Reverse Current (Rated DC Voltage, $T_C=25^\circ\text{C}$) (Rated DC Voltage, $T_C=125^\circ\text{C}$) | I_R | 10 500 | | | | µA |
| Reverse Recovery Time ($I_F=0.5$ A, $I_R=1.0$, $I_r=0.25$ A) | T_{rr} | 35 | | | | ns |
| Typical Junction Capacitance (Reverse Voltage of 4 volts & $f=1$ MHz) | C_p | 120 | | | | pF |

