


Preliminary Data Sheet


Features

- For broadband applications
- Typical 3dB bandwidth of 33.2 MHz
- High attenuation
- Single-ended operation
- Ceramic Surface Mount Package (SMP)
- Small size
- Replaces Sawtek P/N 851937 (BW 3dB=32 MHz)




Package

Surface Mount 9.00 x 7.01 x 1.50 mm



Pin Configuration

Bottom View



Pin No.	Description
4	Output
5	Output return
9	Input
10	Input return
1,2,3,6,7,8	Case ground

Dimensions shown are nominal in millimeters
 All tolerances are ± 0.15 mm except overall
 length and width $+0.10$ mm/ -0.15 mm

Body: Al_2O_3 ceramic
 Lid: Kovar, Ni plated
 Terminations: Au plating 0.5 - 1.0 μ m,
 over a 2 - 6 μ m Ni plating

Preliminary Data Sheet

Electrical Specifications ⁽¹⁾

Operating Temperature Range: ⁽²⁾ 0 to +70 °C


Parameter ⁽³⁾	Minimum	Typical	Maximum	Unit
Center Frequency	-	140	-	MHz
Minimum Insertion Loss	-	21.7	22.5	dB
Lower 1 dB Bandedge ⁽⁴⁾	-	124.29	125.15	MHz
Upper 1 dB Bandedge	154.85	155.88	-	
Lower 3 dB Bandedge ⁽⁴⁾	-	123.42	124.2	MHz
Upper 3 dB Bandedge	155.8	156.64	-	
Lower 40 dB Bandedge ⁽⁴⁾	119.65	120.31	-	MHz
Upper 40 dB Bandedge	-	159.58	160.35	
Amplitude Variation 125.15 - 154.85 MHz	-	0.46	1.10	dB p-p
Phase Linearity 125.15 - 154.85 MHz	-	2.75	6.0	deg p-p
Group Delay Variation 125.15 - 154.85 MHz	-	15.46	30	ns p-p
Absolute Delay	-	0.905	-	μsec
Relative Attenuation ⁽⁴⁾				
15 - 60 MHz	45	56	-	dB
60 - 115 MHz	43	54	-	dB
165 - 200 MHz	42	52	-	dB
200 - 300 MHz	47	58	-	dB
Terminating Source Impedance: ⁽⁵⁾	-	50	-	Ω
Terminating Load Impedance: ⁽⁵⁾	-	50	-	Ω
Substrate Material	-	128 LiNbO ₃	-	-
Temperature Coefficient of Frequency	-	-74	-	ppm/°C

Notes:

1. All specifications are based on the test circuit shown below
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature and manufacturing tolerances
4. All attenuation measurements are measured relative to minimum insertion loss
5. This is the optimum impedance in order to achieve the performance shown

Test Circuit:


Actual matching values may vary due to PCB layout and parasitics




Preliminary Data Sheet

Typical Performance (at +25°C)


Frequency Response




Passband Response




Widespan Response




Phase Response



Input Smith Chart



Output Smith Chart




Preliminary Data Sheet

Maximum Ratings

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating Temperature Range	T	0	+25	+70	°C
Storage Temperature Range	T _{stg}	-40	-	+85	°C

Warnings

- Electrostatic Sensitive Device (ESD) 
- Avoid ultrasonic exposure

Links to Additional Technical Information

[PCB Layout Tips](#)

[Qualification Flowchart](#)

[Soldering Profile](#)

[S-Parameters](#)

[Reel and Packaging Label](#)

[Other Technical Information](#)

Sawtek's liability is limited only to the Surface Acoustic Wave (SAW) component(s) described in this data sheet. Sawtek does not accept any liability for applications, processes, circuits or assemblies which are implemented using any Sawtek component described in this data sheet.

Contact Information



PO Box 609501
 Orlando, FL 32860-9501
 USA

Phone: +1 (407) 886-8860
 Fax: +1 (407) 886-7061
 Email: custservice@sawtek.com
 Web: www.sawtek.com

Or contact one of our worldwide
 Network of [sales offices](#),
[Representatives or distributors](#)