

# **MBR0530**

# **Schottky Rectifier**

### **Features**

- 0.5 Ampere, low forward voltage, less than 430mV
- Compact surface mount package with the same footprint as mini-melf



SOD123 Color Band Denotes Cathode Mark: B3

## Absolute Maximum Ratings \* Ta = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
V <sub>RRM</sub>	Maximum Repetitive Reverse Voltage	30	V
I <sub>F(AV)</sub>	Average Rectified Forward Current	500	mA
I <sub>FSM</sub>	Non Repetitive Peak Forward Current (Surge applied at rated load conditions half wave, single, phase, 60Hz)	5.5	А
T <sub>STG</sub>	Storage Temperature Range	-65 to +150	°C
T <sub>Jmax</sub>	Operating Junction Temperature	-65 to +125	°C

These ratings are limiting values above which the serviceability of any semiconductor device may by impaired.

### **Thermal Characteristics**

Symbol	Parameter	Value	Units
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient *	206	°C/W
$R_{\theta JL}$	Thermal Resistance, Junction to Lead	173	°C/W

<sup>\* 1</sup> inch square pad size on FR-4 board.

## **Electrical Characteristics** $T_C = 25$ °C unless otherwise noted

Symbol	Parameter		Value	Units
V <sub>F</sub>	Forward Voltage	@ $I_F = 100$ mA $I_F = 100$ mA, $T_A = 100$ °C $I_F = 500$ mA $I_F = 500$ mA, $T_A = 100$ °C	375 340 430 420	mV mV mV mV
I <sub>R</sub>	Reverse Current	@ $V_R = 15V$ $V_R = 30V$ $V_R = 30V$ , $T_a = 100$ °C	20 130 5	μΑ μΑ mA

# **Typical Performance Characteristics**

**Figure 1. Forward Voltage Characteristics** 




Figure 2. Reverse Current vs Reverse Voltage





Figure 3. Total Capacitance



#### **TRADEMARKS**

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FAST <sup>®</sup>	ISOPLANAR™	PowerSaver™	SuperSOT™-6
ActiveArray™	FASTr™	LittleFET™	PowerTrench <sup>®</sup>	SuperSOT™-8
Bottomless™	FPS™	MICROCOUPLER™	QFET <sup>®</sup>	SyncFET™
Build it Now™	FRFET™	MicroFET™	QS <sup>TM</sup>	TinyLogic <sup>®</sup>
CoolFET™	GlobalOptoisolator™	MicroPak™	QT Optoelectronics™	TINYOPTO™
CROSSVOLT™	GTO™ <sup>.</sup>	MICROWIRE™	Quiet Series™	TruTranslation™
DOME™	HiSeC™	MSX™	RapidConfigure™	UHC™
EcoSPARK™	I <sup>2</sup> C™	MSXPro™	RapidConnect™	UltraFET <sup>®</sup>
E <sup>2</sup> CMOS™	i-Lo™	OCXTM	μSerDes™	UniFET™
EnSigna™	ImpliedDisconnect™	OCXPro™	ScalarPump™	VCX <sup>TM</sup>
FACT™	IntelliMAX™	OPTOLOGIC <sup>®</sup>	SILENT SWITCHER®	Wire™
FACT Quiet Series™		OPTOPLANAR™	SMART START™	
		PACMAN™	SPM™	
Across the board. Around the world.™		<b>P</b> ∩ <b>P</b> ™	Stealth™	

#### **DISCLAIMER**

The Power Franchise®

Programmable Active Droop™

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

РОР™

Power247™

PowerEdge™

### **LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

### As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Stealth™

SuperFET™

SuperSOT™-3

#### PRODUCT STATUS DEFINITIONS

### **Definition of Terms**

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Rev. I17