


3.1 ϕ Bow-shaped LED


SEL4028 Series

External Dimensions

(Unit: mm)



Directivity (Typical)



Absolute maximum ratings (Ta=25°C)

Symbol	Unit	Rating	Condition
I_F	mA	30	
ΔI_F	mA/°C	-0.45	Above 25°C
I_{FP}	mA	100	f=1kHz, tw \leq 100 μ s
V_R	V	3	
Top	°C	-30 to +85	
Tstg	°C	-30 to +100	

Electrical Optical characteristics (Ta=25°C)

Emitting color	Part Number	Lens color	Forward voltage		Reverse current		Intensity		Peak wavelength		Spectrum half width		Chip material	
			V_F		I_R	V_R	I_v	I_F	λ_P	$\Delta\lambda$	I_F	I_F		
			typ	max										Condition
High-intensity red	SEL4628C-S	Clear	1.7	2.2	10	100	3	200	20	660	10	30	10	GaAlAs
Red	SEL4228C	Clear	1.9	2.5	10	50	3	27	20	630	10	35	10	GaAsP
Amber	SEL4828A	Transparent orange	1.9	2.5	10	50	3	14	10	610	10	35	10	
Orange	SEL4928A	Transparent orange	1.9	2.5	10	50	3	14	10	587	10	33	10	
Yellow	SEL4728K	Transparent yellow	2.0	2.5	10	50	3	30	10	570	10	30	10	GaP
Green	SEL4428E	Transparent green	2.0	2.5	10	50	3	63	20	560	10	20	10	
Deep green	SEL4428B-TG	Transparent dark blue	2.0	2.5	10	50	3	18	20	558	10	20	10	
Pure green	SEL4528C	Clear	2.0	2.5	10	50	3	30	20	555	10	20	10	