

SPECIFICATIONS

FREQUENCY RANGE: DC TO 1 GHz

ATTENUATION RANGE: 0 TO 81 dB IN .1 dB STEPS

IMPEDANCE: 50 OHMS

ATTENUATION ACCURACY:

DC TO 30 MHz:	0 TO 1 dB, ± 0.02 dB
	1 TO 10 dB, ± 0.1 dB
	10 TO 81 dB, ± 0.2 dB
30 TO 500 MHz:	0 TO 1 dB, ± 0.04 dB
	1 TO 10 dB, ± 0.2 dB
	10 TO 81 dB, ± 0.5 dB
500 TO 1000 MHz:	0 TO 1 dB, ± 0.06 dB
	1 TO 10 dB, ± 0.3 dB
	10 TO 81 dB, ± 0.8 dB


VSWR: DC TO 30 MHz, 1.1:1 MAXIMUM

30 TO 500 MHz, 1.3:1 MAXIMUM

500 TO 1000 MHz, 1.5:1 MAXIMUM

AVERAGE POWER: 1 WATT WITH 1000 WATTS PEAK

OPERATING TEMPERATURE: -20°C TO 85°C

		PASTERNAK ENTERPRISES, LLC P.O. BOX 16759, IRVINE, CA 92623 PHONE (949) 261-1920 FAX (949) 261-7451 WEB ADDRESS: www.pasternack.com E-MAIL ADDRESS: sales@pasternack.com	
		ESTABLISHED 1972 COAXIAL & FIBER OPTICS	
DWG TITLE PE7058-1		DES. THREE STAGE BENCH MOUNT ROTARY ATTENUATOR FREQUENCY RANGE: DC TO 1 GHz	
SIZE A	FSCM NO. 53919	CAD FILE 082202	SCALE N/A
NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.			

www.DataSheet4U.com