


200 V - 1,000 V Single Phase Bridge

1.4 A - 1.5 A Forward Current

70 ns - 3000 ns Recovery Time

1102B - 1110B
1102FB - 1110FB
1102UFB - 1110UFB




ELECTRICAL CHARACTERISTICS AND MAXIMUM RATINGS

Part Number	Working Reverse Voltage (V _{rwm})	Average Rectified Current @TC (I _o)		Reverse Current @ V _{rwm} (I _r)		Forward Voltage (V _f)		1 Cycle Surge Current (I _{fsm})	Repetitive Surge Current (I _{frm})	Reverse Recovery Time (1) (T _{rr})	Thermal Impd. θ _{J-C}
		55°C	100°C	25°C	100°C	25°C	Amps	25°C	25°C	25°C	°C/W
		Amps	Amps	µA	µA	Volts		Amps	Amps	ns	
1102B 1106B 1110B	200 600 1000	1.5 1.5 1.5	1.0 1.0 1.0	1.0 1.0 1.0	25 25 25	1.1 1.1 1.1	1.0 1.0 1.0	50 50 50	10 10 10	3000 3000 3000	22.5 22.5 22.5
1102FB 1106FB 1110FB	200 600 1000	1.5 1.5 1.5	1.0 1.0 1.0	1.0 1.0 1.0	25 25 25	1.3 1.3 1.3	1.0 1.0 1.0	25 25 25	6.0 6.0 6.0	150 150 150	22.5 22.5 22.5
1102UFB 1106UFB 1110UFB	200 600 1000	1.4 1.4 1.4	0.9 0.9 0.9	1.0 1.0 1.0	25 25 25	1.7 1.7 1.7	1.0 1.0 1.0	25 25 25	5.0 5.0 5.0	70 70 70	22.5 22.5 22.5

(1)T_{rr} Testing: I_f=0.5A, I_r=1.0A, I_{rr}=0.25A *Op. Temp.= -55°C to +150°C Stg. Temp.= -55°C to +150°C

10



Dimensions: In. (mm) • All temperatures are ambient unless otherwise noted. • Data subject to change without notice.



VOLTAGE MULTIPLIERS INC.
 8711 W. Roosevelt Ave.
 Visalia, CA 93291

TEL 559-651-1402
 FAX 559-651-0740
www.voltagemultipliers.com

1102B - 1110B • 1102FB - 1110FB • 1102UFB - 1110UFB

