



# SS32 THRU SS310

## 3.0 AMPS. Surface Mount Schottky Barrier Rectifiers



Voltage Range  
20 to 100 Volts  
Current  
3.0 Amperes


### Features

- ✧ For surface mounted application
- ✧ Metal to silicon rectifier, majority carrier conduction
- ✧ Low forward voltage drop
- ✧ Easy pick and place
- ✧ High surge current capability
- ✧ Plastic material used carriers Underwriters Laboratory Classification 94V-0
- ✧ Epitaxial construction
- ✧ High temperature soldering:  
260°C / 10 seconds at terminals

### Mechanical Data

- ✧ Case: Molded plastic
- ✧ Terminals: Solder plated
- ✧ Polarity: Indicated by cathode band
- ✧ Packaging: 16mm tape per EIA STD RS-481
- ✧ Weight: 0.21 gram

### SMC/DO-214AB



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	SS 32	SS 33	SS 34	SS 35	SS 36	SS 39	SS 310	Units	
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	20	30	40	50	60	90	100	V	
Maximum RMS Voltage	$V_{RMS}$	14	21	28	35	42	63	70	V	
Maximum DC Blocking Voltage	$V_{DC}$	20	30	40	50	60	90	100	V	
Maximum Average Forward Rectified Current at $T_A$ (See Fig. 1)	$I_{(AV)}$	3.0							A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	100							A	
Maximum Instantaneous Forward Voltage (Note 1) @ 3.0A	$V_F$	0.5		0.75		0.85		V		
Maximum DC Reverse Current @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=100^\circ\text{C}$	$I_R$	0.5					0.6		mA	
		20		10.0		20				
Typical Thermal Resistance ( Note 2 )	$R_{\theta_{JL}}$	17							$^\circ\text{C}/\text{W}$	
	$R_{\theta_{JA}}$	55								
Operating Temperature Range	$T_J$	-55 to +125			-55 to +150				$^\circ\text{C}$	
Storage Temperature Range	$T_{STG}$	-55 to +150								$^\circ\text{C}$

Notes: 1. Pulse Test with PW=300 usec, 1% Duty Cycle

2. Measured on P.C.Board with 0.6 x 0.6"(16 x 16mm) Copper Pad Areas.

## RATINGS AND CHARACTERISTIC CURVES (SS32 THRU SS310)

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE




FIG.6- TYPICAL TRANSIENT THERMAL IMPEDANCE

