



Bias Resistor Transistor

NPN Silicon

 **Lead(Pb)-Free**



MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	VCEO	50	Vdc
Collector-Base Voltage	VCBO	50	Vdc
Collector Current-Continuous	Ic	100	mAdc

THERMAL CHARACTERISTICS

Characteristics	Symbol	Value	Unit
Total Device Dissipation FR-5 Board (1) TA = 25°C Derate above 25°C	PD	246 1.6	mW mW / °C
Thermal Resistance, Junction to Ambient (1)	R _{θJA}	625	°C/W
Junction and Storage, Temperature	T _{J,Tstg}	-65 to +150	°C

1.FR-4 @ minimum pad

Device Marking and Resistor Values

Device	Marking	R1(k)	R2(k)	Device	Marking	R1(k)	R2(k)
MMUN2211	A8A	10	10	MMUN2232	A8J	4.7	4.7
MMUN2212	A8B	22	22	MMUN2233	A8K	4.7	47
MMUN2213	A8C	47	47	MMUN2234	A8L	22	47
MMUN2214	A8D	10	47	MMUN2235	A8M	2.2	47
MMUN2215	A8E	10	∞	MMUN2238	A8R	2.2	∞
MMUN2216	A8F	4.7	∞	MMUN2241	A8U	100	∞
MMUN2230	A8G	1.0	1.0				
MMUN2231	A8H	2.2	2.2				

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ C$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector-Base Cutoff Current ($V_{CB} = 50 V$, $I_E = 0$)	I_{CBO}	-	-	100	nAdc
Collector-Emitter Cutoff Current ($V_{CE} = 50 V$, $I_B = 0$)	I_{CEO}	-	-	500	nAdc
Emitter-Base Cutoff Current ($V_{EB} = 6.0 V$, $I_C = 0$)	I_{EBO}	-	-	0.5	mAdc
MMUN2211		-	-	0.2	
MMUN2212		-	-	0.1	
MMUN2213		-	-	0.2	
MMUN2214		-	-	0.9	
MMUN2215		-	-	1.9	
MMUN2216		-	-	4.3	
MMUN2230		-	-	2.3	
MMUN2231		-	-	1.5	
MMUN2232		-	-	0.18	
MMUN2233		-	-	0.13	
MMUN2234		-	-	0.2	
MMUN2235		-	-	4.0	
MMUN2238		-	-	0.1	
MMUN2241		-	-	-	
Collector-Base Breakdown Voltage ($I_C = 10 mA$, $I_E = 0$)	$V_{(BR)CBO}$	50	-	-	Vdc
Collector-Emitter Breakdown Voltage (Note 2.) ($I_C = 2.0 mA$, $I_B = 0$)	$V_{(BR)CEO}$	50	-	-	Vdc

ON CHARACTERISTICS (Note 2.)

DC Current Gain ($V_{CE} = 10 V$, $I_C = 5.0 mA$)	MMUN2211 MMUN2212 MMUN2213 MMUN2214 MMUN2215 MMUN2216 MMUN2230 MMUN2231 MMUN2232 MMUN2233 MMUN2234 MMUN2235 MMUN2238 MMUN2241	h_{FE}	35 60 80 80 160 160 3.0 8.0 15 80 80 80 160 160	60 100 140 140 350 350 5.0 15 30 200 150 140 350 350	-	
Collector-Emitter Saturation Voltage ($I_C = 10 mA$, $I_B = 0.3 mA$) ($I_C = 10 mA$, $I_B = 5 mA$) MMUN2230/MMUN2231 ($I_C = 10 mA$, $I_B = 1 mA$) MMUN2215/MMUN2216/MMUN2232 MMUN2233/MMUN2234/MMUN2235/MMUN2238		$V_{CE(sat)}$	-	-	0.25	Vdc
Output Voltage (on) ($V_{CC} = 5.0 V$, $V_B = 2.5 V$, $R_L = 1.0 k\Omega$) ($V_{CC} = 5.0 V$, $V_B = 3.5 V$, $R_L = 1.0 k\Omega$) ($V_{CC} = 5.0 V$, $V_B = 5.0 V$, $R_L = 1.0 k\Omega$)	MMUN2211 MMUN2212 MMUN2213 MMUN2214 MMUN2215 MMUN2216 MMUN2230 MMUN2231 MMUN2232 MMUN2233 MMUN2234 MMUN2235 MMUN2238 MMUN2241	V_{OL}	- - - - - - - - - - - - - -	- - - - - - - - - - - - - -	0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2	Vdc

2. Pulse Test: Pulse Width < 300 ms, Duty Cycle < 2.0 %.

MMUN2211 Series



ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Typ	Max	Unit
ON CHARACTERISTICS (Note 2) (Continued)					
Output Voltage (off) ($V_{CC} = 5.0 \text{ V}, V_B = 0.5 \text{ V}, R_L = 1.0 \text{ k}\Omega$) ($V_{CC} = 5.0 \text{ V}, V_B = 0.050 \text{ V}, R_L = 1.0 \text{ k}\Omega$) ($V_{CC} = 5.0 \text{ V}, V_B = 0.25 \text{ V}, R_L = 1.0 \text{ k}\Omega$)	V_{OH}	4.9	-	-	Vdc
MMUN2230 MMUN2215 MMUN2216 MMUN2233 MMUN2238					
Input Resistor	R_1				$\text{k}\Omega$
MMUN2211 MMUN2212 MMUN2213 MMUN2214 MMUN2215 MMUN2216 MMUN2230 MMUN2231 MMUN2232 MMUN2233 MMUN2234 MMUN2235 MMUN2238 MMUN2241		7.0 15.4 32.9 7.0 7.0 3.3 0.7 1.5 3.3 3.3 15.4 1.54 1.54 70	10 22 47 10 10 4.7 1.0 2.2 4.7 4.7 22 2.2 2.2 100	13 28.6 61.1 13 13 6.1 1.3 2.9 6.1 6.1 28.6 2.86 2.86 100	
Resistor Ratio	R_1/R_2				
MMUN2211/MMUN2212/MMUN2213 MMUN2214 MMUN2215/MMUN2216/MMUN2238 MMUN2241 MMUN2230/MMUN2231/MMUN2232 MMUN2233 MMUN2234 MMUN2235		0.8 0.17 - - 0.8 0.055 0.38 0.038	1.0 0.21 - - 1.0 0.1 0.47 0.047	1.2 0.25 - - 1.2 0.185 0.56 0.056	

2. Pulse Test: Pulse Width < 300 μs , Duty Cycle < 2.0%

TYPICAL ELECTRICAL CHARACTERISTICS MMUN2211




Figure 1. Derating Curve




Figure 2. $V_{CE(\text{sat})}$ vs. I_C

TYPICAL ELECTRICAL CHARACTERISTICS

MMUN2212




Figure 3. DC Current Gain




Figure 4. Output Capacitance




Figure 5. Output Current vs. Input Voltage




Figure 6. Input Voltage vs. Output Current

MMUN2211




Figure 7. $V_{CE(sat)}$ vs. I_C









Figure 8. DC Current Gain




TYPICAL ELECTRICAL CHARACTERISTICS MMUN2212





MMUN2213



TYPICAL ELECTRICAL CHARACTERISTICS MMUN2213



MMUN2214



TYPICAL ELECTRICAL CHARACTERISTICS MMUN2214





Figure 19. Output Capacitance

Figure 20. Output Current vs. Input Voltage




Figure 21. Input Voltage vs. Output Current

MMUN2232




Figure 22. $V_{CE(sat)}$ vs. I_C




Figure 23. DC Current Gain

TYPICAL ELECTRICAL CHARACTERISTICS

MMUN2232




Figure 24. Output Capacitance




Figure 25. Output Current vs. Input Voltage




Figure 26. Output Voltage vs. Input Current

MMUN2233




Figure 27. $V_{CE(sat)}$ vs. I_C




Figure 28. DC Current Gain

MMUN2211 Series

TYPICAL APPLICATIONS FOR NPN BRTs




Figure 32. Level Shifter: Connects 12 or 24 Volt Circuits to Logic




Figure 33. Open Collector Inverter: Inverts the Input Signal





Figure 34. Inexpensive, Unregulated Current Source

SOT-23 Package Outline Dimension



SOT-23		
Dim	Min	Max
A	0.35	0.51
B	1.19	1.40
C	2.10	3.00
D	0.85	1.05
E	0.46	1.00
G	1.70	2.10
H	2.70	3.10
J	0.01	0.13
K	0.89	1.10
L	0.30	0.61
M	0.076	0.25