Rail Mounted Terminal Blocks 1039980000

When good enough just isn't good enoug
Weidmüller 3

WTR 2.5/ZZ

Email to a Friend

View Catalog Page

View Line Drawing




Representative Photo

Technical Information

Clamping Type Screw Clamp Series W Series Rail Type TS 35 Function Disconnect Configuration Lever Wire Size 2.5 mm² Current 14 A 400 V Voltage Color/Material Blue Wemid

Special Requirements



Technical Data

	UL	CSA	VDE
Rated Voltage			400 V
Rated Current			14 A
Wire Size			2.5 mm ²

Additional Data

Width/Length/Height mm (in.) 5/60/49 (.2"/2.36"/1.93")

Insulation Stripping Length mm (in.) 10 (.39")

Torque Nm (lb. in) 0.6 (5.2)

Clamping Screw M 3

Flammability Class UL 94 (V0)

Suggested Accessories

DIN-rail Diode plug

End plate/partition (WAP/WTW)

Ferrules

Markers (SchT)

Marking pens
Marking system (WS/ZS)
Marking tags (DEK)
Mounting brackets
Test plugs/socket
Tools
ZQV jumpers

Product Liability The above information describes our products. It does not constitute guaranteed properties and is not intended to a the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot be completely ruled out. Techni data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from

Weidmüller - North America United States 001 (800) 849-9343 Canada 001 (800) 268-4080

10

Weidmüller - Germany Telephone operator 0049 (-5252) 960-0