




**DB LECTRO**<sup>®</sup>  
COMPOSANTS ÉLECTRONIQUES  
ELECTRONIC COMPONENTS

## 6550-7241-AU-50 650nm 5 mW Laser Diodes AUTO PACKAGE(REGROWTH)

### Specifications

Device            Laser Diode  
Package Type    TO-18( 5.6mm)



### Absolute Maximum Ratings(Tc=25 °C)

Characteristics	Symbols	Ratings	Units
Optical Output	Po	<b>7</b>	mW
Reverse Voltage	Laser Vr	<b>2</b>	V
	PIN PD Vr(PIN)	<b>30</b>	V
Operating Temperature	Top	-10 +50	
Storage Temperature	Tstg	-40 +85	

### Electrical and optical Characteristics(Tc=25 °C)

Characteristics	Symbols	Conditions	Min.	Typ.	Max.	Units
Threshold Current	Ith	-	-	<b>20</b>	<b>30</b>	mA
Operating Current	Iop	Po=5mW	-	<b>30</b>	<b>40</b>	mA
Operating Voltage	Vop	Po=5mW	-	<b>2.2</b>	<b>2.6</b>	Volts
Slope Efficiency		2mW	<b>0.3</b>	<b>0.7</b>	<b>1</b>	mW/mA
		I(5mW)-I(3mW)				
Monitor Current	Im	Po=5mW	-	<b>0.2</b>	<b>0.8</b>	mA
Beam Divergence (FWHM)	Parallel	//	Po=5mW	<b>5</b>	<b>8</b>	deg.
	Prependicular		Po=5mW	<b>25</b>	<b>33</b>	deg.
Parallel Deviation Angle		//	Po=5mW	<b>-3</b>	-	deg.
Perpendicular Deviation Angle			Po=5mW	<b>-3</b>	-	deg.
Emission Point Accuracy	X	Po=5mW	<b>-80</b>	-	<b>80</b>	um
	Y	Po=5mW	<b>-80</b>	-	<b>80</b>	um
	Z	Po=5mW	<b>-80</b>	-	<b>80</b>	um
Lasing Wavelength		Po=5mW	<b>645</b>	<b>650</b>	<b>660</b>	nm

Im is sorting by custom's need

// and        are defined as the angle within which the intensity is 50% of the peak value.