

GHB-3M35-R

Features


- ✓ LOW POWER CONSUMPTION.
- ✓ SOLID STATE BLUE LIGHT SOURCE

Description

The Hyper Red source color devices are made with DH InGaAlP on GaAs substrate Light Emitting Diode.

T-1 (3mm) SOLID STATE LAMP

Package Dimensions



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is $.25(0.01)$ unless otherwise noted.
3. Lead spacing is measured where the lead emerge package.
4. Specifications are subject to change without notice.

Selection Guide

Part No.	Dice	Lens Type	Iv (mcd) @ 20mA		Viewing Angle
			Min.	Typ.	
GHB-3M35-R	HYPER RED (InGaAIP)	WATER CLEAR	900	1300	34

Note:

1 1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

Electrical / Optical Characteristics at T_A=25 C

Symbol	Parameter	Device	Typ.	Max.	Units	Test Conditions
peak	Peak Wavelength		640		nm	I _F = 20mA
D	Dominate Wavelength		630		nm	I _F = 20mA
1/2	Spectral Line Half-width		25		nm	I _F = 20mA
C	Capacitance		45		pF	V _F = 0V; f = 1MHz
V _F	Forward Voltage		2.9	2.5	V	I _F = 20mA
I _R	R everse Current			10	uA	V _R = 5V

Absolute Maximum Ratings at T_A=25 C

Parameter	Hyper Red	Units
Power dissipation	150	mW
DC Forward Current	30	m A
Peak Forward Current [1]	200	m A
Reverse Voltage	5	V
Operating/Storage Temperature	-40 C To +85 C	
Lead Solder Temperature [2]	260 C For 5 Seconds	

Notes:

1. 1/10 Duty Cycle, 0.1ms Pulse Width.
2. 2mm below package base.

