


#### DESCRIPTION

MYB64D is yellow LED lamp encapsulated in a 2mmX5mm flangeless rectangular bars with yellow diffused lens.



#### ABSOLUTE MAXIMUM RATINGS

Power Dissipation @ Ta=25°C  
 Forward Current, DC (IF)  
 Reverse Voltage  
 Operating & Storage Temperature Range  
 Lead Soldering Temperature (1/16" from body)

60mW  
 20mA  
 5V  
 -55 to +100°C  
 260°C for 5 sec.

- All dimension in mm(inch)
- No Scale
- Tol. : +/-0.3mm

#### ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Forward Voltage	VF			3.0	V	IF=20mA
Reverse Breakdown Voltage	BVR	5			V	IR=100μA
Luminous Intensity	IV	4	7		mcd	IF=20mA
Peak Wavelength	λp		585		nm	IF=20mA
Spectral Line Half Width	Δλ		35		nm	IF=20mA



MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex:43510 Micro Hx. Tel: 2343 0181-5