

## SIPMOS<sup>®</sup> Small-Signal-Transistor


### Feature

- N-Channel
- Enhancement mode
- Logic Level
- dv/dt rated

### Product Summary

$V_{DS}$	60	V
$R_{DS(on)}$	5	$\Omega$
$I_D$	0.23	A

SOT-323



Type	Package	Ordering Code	Tape and Reel Information	Marking
SN7002W	SOT-323	Q67042-S4186	E6327: 3000 pcs/reel	ssN
SN7002W	SOT-323	Q67042-S4193	E6433: 10000 pcs/reel	ssN

**Maximum Ratings**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current $T_A=25^\circ\text{C}$	$I_D$	0.23	A
$T_A=70^\circ\text{C}$		0.18	
Pulsed drain current $T_A=25^\circ\text{C}$	$I_D$ puls	0.92	
Reverse diode dv/dt $I_S=0.23\text{A}, V_{DS}=48\text{V}, di/dt=200\text{A}/\mu\text{s}, T_{jmax}=150^\circ\text{C}$	dv/dt	6	kV/ $\mu\text{s}$
Gate source voltage	$V_{GS}$	$\pm 20$	V
ESD Sensitivity (HBM) as per MIL-STD 883		Class 1	
Power dissipation $T_A=25^\circ\text{C}$	$P_{tot}$	0.5	W
Operating and storage temperature	$T_j, T_{stg}$	-55... +150	$^\circ\text{C}$
IEC climatic category; DIN IEC 68-1		55/150/56	

**Final data****SN7002W****Thermal Characteristics**

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Characteristics</b>					
Thermal resistance, junction - ambient at minimal footprint	$R_{thJS}$	-	-	250	K/W

**Electrical Characteristics**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	

**Static Characteristics**

Drain-source breakdown voltage $V_{GS}=0$ , $I_D=250\mu\text{A}$	$V_{(BR)DSS}$	60	-	-	V
Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D=26\mu\text{A}$	$V_{GS(\text{th})}$	0.8	1.4	1.8	
Zero gate voltage drain current $V_{DS}=60\text{V}$ , $V_{GS}=0$ , $T_j=25^\circ\text{C}$ $V_{DS}=60\text{V}$ , $V_{GS}=0$ , $T_j=150^\circ\text{C}$	$I_{DSS}$	-	-	0.1 5	$\mu\text{A}$
Gate-source leakage current $V_{GS}=20\text{V}$ , $V_{DS}=0$	$I_{GSS}$	-	-	10	nA
Drain-source on-state resistance $V_{GS}=4.5\text{V}$ , $I_D=0.2\text{A}$	$R_{DS(\text{on})}$	-	4.1	7.5	$\Omega$
Drain-source on-state resistance $V_{GS}=10\text{V}$ , $I_D=0.23\text{A}$	$R_{DS(\text{on})}$	-	2.3	5	

**Electrical Characteristics**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Dynamic Characteristics**

Transconductance	$g_{fs}$	$V_{DS} \geq 2 * I_D * R_{DS(on)max}$ , $I_D = 0.18\text{A}$	0.1	0.21	-	S
Input capacitance	$C_{iss}$	$V_{GS}=0$ , $V_{DS}=25\text{V}$ , $f=1\text{MHz}$	-	34	45	pF
Output capacitance	$C_{oss}$		-	7.2	9.6	
Reverse transfer capacitance	$C_{rss}$		-	3	4.5	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=30\text{V}$ , $V_{GS}=10\text{V}$ , $I_D=0.23\text{A}$ , $R_G=6\Omega$	-	2.4	3.6	ns
Rise time	$t_r$		-	2.8	4.2	
Turn-off delay time	$t_{d(off)}$		-	6	9	
Fall time	$t_f$		-	8.5	12.75	

**Gate Charge Characteristics**


Gate to source charge	$Q_{gs}$	$V_{DD}=48\text{V}$ , $I_D=0.23\text{A}$	-	0.11	0.17	nC
Gate to drain charge	$Q_{gd}$		-	0.42	0.63	
Gate charge total	$Q_g$	$V_{DD}=48\text{V}$ , $I_D=0.23\text{A}$ , $V_{GS}=0$ to $10\text{V}$	-	1	1.5	
Gate plateau voltage	$V_{(plateau)}$	$V_{DD}=48\text{V}$ , $I_D = 0.23 \text{ A}$	-	3.4	-	V

**Reverse Diode**

Inverse diode continuous forward current	$I_S$	$T_A=25^\circ\text{C}$	-	-	0.23	A	
Inv. diode direct current, pulsed	$I_{SM}$		-	-	0.92		
Inverse diode forward voltage	$V_{SD}$	$V_{GS}=0$ , $I_F=0.23\text{A}$		-	0.85	1.2	V
Reverse recovery time	$t_{rr}$	$V_R=30\text{V}$ , $I_F=I_S$ ,		-	10.8	16.2	ns
Reverse recovery charge	$Q_{rr}$	$di_F/dt=100\text{A}/\mu\text{s}$		-	3.2	4.8	nC

### 1 Power dissipation


$$P_{\text{tot}} = f(T_A)$$



### 2 Drain current

$$I_D = f(T_A)$$


parameter:  $V_{GS} \geq 10$  V



### 3 Safe operating area

$$I_D = f(V_{DS})$$


parameter :  $D = 0$ ,  $T_A = 25$  °C



### 4 Transient thermal impedance

$$Z_{\text{thJA}} = f(t_p)$$


parameter :  $D = t_p/T$



**5 Typ. output characteristic**


$$I_D = f(V_{DS})$$

parameter:  $T_J = 25^\circ\text{C}$ ,  $V_{GS}$


**6 Typ. drain-source on resistance**


$$R_{DS(on)} = f(I_D)$$

parameter:  $T_J = 25^\circ\text{C}$ ,  $V_{GS}$


**7 Typ. transfer characteristics**


$$I_D = f(V_{GS}); V_{DS} \geq 2 \times I_D \times R_{DS(on)\max}$$

parameter:  $T_J = 25^\circ\text{C}$


**8 Typ. forward transconductance**

$$g_{fs} = f(I_D)$$


parameter:  $T_J = 25^\circ\text{C}$



**(.) Drain-source on-state resistance**


$$R_{DS(on)} = f(T_j)$$

parameter :  $I_D = 0.23 \text{ A}$ ,  $V_{GS} = 10 \text{ V}$


**10 Typ. gate threshold voltage**


$$V_{GS(th)} = f(T_j)$$

parameter:  $V_{GS} = V_{DS}$ ;  $I_D = 26 \mu\text{A}$


**11 Typ. capacitances**


$$C = f(V_{DS})$$

parameter:  $V_{GS}=0$ ,  $f=1 \text{ MHz}$ ,  $T_j = 25 \text{ }^\circ\text{C}$


**12 Forward character. of reverse diode**


$$I_F = f(V_{SD})$$

parameter:  $T_j$




**13 Typ. gate charge**

$V_{GS} = f(Q_G)$ ; parameter:  $V_{DS}$ ,  
 $I_D = 0.16 \text{ A pulsed}, T_j = 25^\circ\text{C}$


**14 Drain-source breakdown voltage**

$V_{(BR)DSS} = f(T_j)$





**Published by**  
**Infineon Technologies AG,**  
**Bereichs Kommunikation**  
**St.-Martin-Strasse 53,**  
**D-81541 München**  
© Infineon Technologies AG 1999  
All Rights Reserved.

**Attention please!**

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

**Information**

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives worldwide (see address list).

**Warnings**

Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.