

TPA-13-6035

Power Amplifier

6 GHz - 13 GHz

This Power Amplifier offers exceptional performance over the band 6 GHz to 13 GHz with 30 dBm P1dB output power and 21 dB Gain.

Teledyne Microwave amplifiers are balanced or feedback designs and manufactured with the latest MIC & MMIC technology. The GaAs FET's used in these amplifiers are well established proven devices from multiple sources.

Teledyne Microwave offers a complete line of Narrow and broadband Amplifiers covering the frequency range 500 MHz to 40 GHz. These products are available in either connectorized packages or as modules. For a complete list of these products and more, please visit our website.

Other products from Teledyne Microwave include:
Transceivers, Synthesizers, and YIG Products



Specifications:

Model Number: TPA-13-6035

Frequency Range: 6 GHz – 13 GHz

Gain (min): 21 dB

Gain Vs Temp at any Frequency: This Amplifier is not Temperature Compensated

Noise Figure (max): 14 dB

Output Power @ 1dB Compression: 30 dBm

Gain Flatness Vs Frequency: +/-1 dB

3rd Order Intercept (Typ): 36 dBm

Power Supply:

Input Voltage: 11.5 to 15 VDC

Current @ 12 VDC (typ): 3320 mA

Current @ 12 VDC (max): Contact Factory

Case Type (See attached Outline): HPX8

Temperature Range: +25C



**TELEDYNE
MICROWAVE**

ISO 9001:2000

1274 Terra Bella Avenue, Mountain View, CA 94043 • PHN# 800.832.6869 or +1.650.962.6944 • FAX# 650.962.6845
www.teledynemicrowave.com • microwave@teledyne.com

Power Amplifier

6 GHz - 13 GHz



ISO 9001:2000

08/05