


### Features

- Glass Passivated Die Construction
- Low Forward Voltage Drop, High Current Capability
- Surge Overload Rating to 50A Peak
- Ideal for Printed Circuit Boards
- Case to Terminal Isolation Voltage 1500V
- UL Listed Under Recognized Component Index, File Number E94661
- Lead Free Finish, RoHS Compliant (DC 514+) (Note 3)**



WOG		
Dim	Min	Max
A	8.84	9.86
B	4.00	4.60
C	27.90	
D	25.40	
E	0.71	0.81
G	4.60	5.60
<b>All Dimensions in mm</b>		

### Mechanical Data

- Case: WOG
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish Silver. Plated Leads Solderable per MIL-STD-202, Method 208 (E3)
- Polarity: As marked on Body
- Marking: Type Number
- Weight: 1.3 grams (approximate)

### Maximum Ratings and Electrical Characteristics @ T<sub>A</sub> = 25 C unless otherwise specified

Single phase, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

Characteristic	Symbol	W005G	W01G	W02G	W04G	W06G	W08G	W10G	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	$V_{RRM}$ $V_{RWM}$ $V_R$	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	280	420	560	700	V
Average Rectified Output Current (Note 1) @ T <sub>A</sub> = 25 C	$I_O$	1.5							A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load per element	$I_{FSM}$	50							A
Forward Voltage (per element) @ I <sub>F</sub> = 1.5A	$V_{FM}$	1.0							V
Peak Reverse Current @ T <sub>A</sub> = 25 C at Rated DC Blocking Voltage @ T <sub>A</sub> = 125 C	$I_{RM}$	5.0 500							μA
Typical Total Capacitance (Note 2)	$C_T$	12							pF
Typical Thermal Resistance Junction to Case (Note 1)	$R_{JC}$	84							C/W
Operating and Storage Temperature Range	$T_j, T_{STG}$	-65 to +150							C

- Notes: 1. Thermal resistance from junction to case mounted on PC board with 13 x 13mm (0.03mm thick) land areas.  
2. Per element, measured at 1.0MHz and applied reverse voltage of 4.0V DC.  
3. EC Directive 2002/95/EC(RoHS) revision 13.2.2003. Glass and High Temperature Solder Exemptions Applied, see *EU Directive Annex Notes 5 and 7.*




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Max Non-Repetitive Surge Current




Fig. 4 Typical Total Capacitance




Fig. 5 Typical Reverse Characteristics

**Ordering Information** (Note 4)

<b>Device</b>	<b>Packaging</b>	<b>Shipping</b>
W005G	WOG	1K Bulk
W01G	WOG	1K Bulk
W02G	WOG	1K Bulk
W04G	WOG	1K Bulk
W06G	WOG	1K Bulk
W08G	WOG	1K Bulk
W10G	WOG	1K Bulk

Notes: 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.