



# BC546,BC547,BC548 SERIES

## NPN GENERAL PURPOSE TRANSISTOR

**VOLTAGE** 30V/45V/65V **POWER** 625 mWatts


### FEATURES

- NPN epitaxial silicon, planar design
- Collector current  $I_C = 100\text{mA}$
- Complimentary (PNP) device:BC556,BC557,BC558 Series
- Pb free product :99% Sn above can meet RoHS environment substance directive request

### MECHANICAL DATA

- Case: TO-92
- Terminals: Solderable per MIL-STD-202, Method 208
- Approx Weight : 0.02grams
- Device Marking :

BC546A=546A	BC546B=546B	-
BC547A=547A	BC547B=547B	BC547C=547C
BC548A=548A	BC548B=548B	BC548C=548C



### ABSOLUTE MAXIMUM RATINGS

PARAMETER	Symbol	Value	Units
Collector - Emitter Voltage	$V_{CEO}$	65 45 30	V
Collector - Base Voltage	$V_{CBO}$	80 50 30	V
Emitter - Base Voltage	$V_{EBO}$	6.0 6.0 5.0	V
Collector Current - Continuous	$I_C$	100	mA
Max Power Dissipation	$P_{TOT}$	625	mW
Storage Temperature	$T_{STG}$	-55 to 150	°C
Junction Temperature	$T_J$	-55 to 150	°C

### THERMAL CHARACTERISTICS

PARAMETER	Symbol	Value	Units
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	200	°C/W



# BC546,BC547,BC548 SERIES

## ELECTRICAL CHARACTERISTICS (T<sub>j</sub>=25°C, unless otherwise noted)

PARAMETER	Symbol	MIN.	TYP.	MAX.	Units
Collector - Emitter Breakdown Voltage (I <sub>c</sub> =10mA, I <sub>b</sub> =0)	BC546A,B BC547A,B,C BC548A,B,C V <sub>(BR)</sub> CEO	65 45 30	-	-	V
Collector - Base Breakdown Voltage (I <sub>c</sub> =10uA, I <sub>e</sub> =0)	BC546A,B BC547A,B,C BC548A,B,C V <sub>(BR)</sub> CBO	80 50 30	-	-	V
Emitter - Base Breakdown Voltage (I <sub>e</sub> =10uA, I <sub>c</sub> =0)	BC546A,B BC547A,B,C BC548A,B,C V <sub>(BR)</sub> EBO	6.0 6.0 5.0	-	-	V
Emitter-Base Cutoff Current (V <sub>EB</sub> =5V)	I <sub>EBO</sub>	-	-	100	nA
Collector-Base Cutoff Current(V <sub>CB</sub> =30V,I <sub>E</sub> =0)	T <sub>j</sub> =150°C I <sub>CBO</sub>	- -	- -	15 5.0	nA uA
DC Current Gain (I <sub>c</sub> =10uA, V <sub>CE</sub> =5V)	BC546A,B BC547A,B,C BC548A,B,C h <sub>FE</sub>	- - -	90 150 270	- - -	-
(I <sub>c</sub> =2.0mA, V <sub>CE</sub> =5V)	BC546A,B BC547A,B,C BC548A,B,C	110 200 420	180 290 520	220 450 800	-
Collector - Emitter Saturation Voltage (I <sub>c</sub> =10mA,I <sub>b</sub> =0.5mA) (I <sub>c</sub> =100mA,I <sub>b</sub> =5.0mA)	V <sub>CE(SAT)</sub>	- -	- -	0.25 0.6	V
Base - Emitter Saturation Voltage (I <sub>c</sub> =10mA,I <sub>b</sub> =0.5mA) (I <sub>c</sub> =100mA,I <sub>b</sub> =5.0mA)	V <sub>BE(SAT)</sub>	- -	0.7 0.9	- -	V
Base - Emitter Voltage (I <sub>c</sub> =2mA V <sub>CE</sub> =0.5mA) (I <sub>c</sub> =10mA, V <sub>CE</sub> =5.0mA)	V <sub>BE(SAT)</sub>	0.58 -	0.660 -	0.70 0.77	V
Collector - Base Capacitance (V <sub>CB</sub> =10V,I <sub>E</sub> =0,f=1MHz)	C <sub>CBO</sub>	-	-	4.5	pF

## LEGAL STATEMENT


### Copyright PanJit International, Inc 2005

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.




# BC546,BC547,BC548 SERIES


ELECTRICAL CHARACTERISTICS CURVE BC546A,BC547A,BC548A ONLY




**Fig. 1. Typical  $I_{CB0}$  vs.**




**Fig. 2. Typical  $h_{FE}$  vs.**




**Fig. 3. Typical  $V_{BE(ON)}$  vs.**



**Fig. 4. Typical  $V_{CE(SAT)}$  vs.**



**Fig. 5. Typical  $V_{BE(SAT)}$  vs.**




**Fig. 6. Typical Capacitances vs.**




# BC546,BC547,BC548 SERIES


ELECTRICAL CHARACTERISTICS CURVE BC546B,BC547B,BC548B ONLY




**Fig. 1. Typical  $I_{CBO}$  vs. Junction Temperature**




**Fig. 2. Typical  $h_{FE}$  vs. Collector Current**




**Fig. 3. Typical  $V_{BE(ON)}$  vs. Collector Current**



**Fig. 4. Typical  $V_{CE(SAT)}$  vs. Collector Current**



**Fig. 5. Typical  $V_{BE(SAT)}$  vs. Collector Current**




**Fig. 6. Typical Capacitances vs. Reverse Voltage**




# BC546,BC547,BC548 SERIES


ELECTRICAL CHARACTERISTICS CURVE BC547C,BC548C ONLY




**Fig. 1. Typical  $I_{CBO}$  vs. Junction**




**Fig. 2. Typical  $h_{FE}$  vs. Collector**




**Fig. 3. Typical  $V_{BE(ON)}$  vs. Collector Current**



**Fig. 4. Typical  $V_{CE(SAT)}$  vs. Collector**



**Fig. 5. Typical  $V_{BE(SAT)}$  vs. Collector**



**Fig. 6. Typical Capacitances vs. Reverse**