

InGaAs PIN PD MODULES

PD-1500 SERIES

InGaAs PIN PHOTODIODE WITH RECEPTACLE

FEATURES

- 2 High responsivity for dual windows at 1310 nm and 1550 nm
- 2 Low dark current
- 2 Quick pulse response

APPLICATION

SDH, ATM, LAN

DESCRIPTION

PD-1500 series are designed for coupling a fiber with high reliable InGaAs PIN photodiodes. PD-1500 series are specially designed as detector for Datacom and Telecom application.

ELECTRICAL AND OPTICAL CHARACTERISTICS (T _C =25°C)						
Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
	Detection Range	λ	1100	-	1650	nm
R	Responsivity	V _R =5V, λ=1300 nm	0.8	0.85	-	A/W
I _{dark}	Dark Current	V _R =5V		0.3	0.7	nA
C	Capacitance	V _R =5V		0.7	0.9	pF
T _r /T _f	Rise/Fall Time	V _R =5V, 10~90%			0.3	ns
BW	Bandwidth	V _R =5V	2			GHz

Absolute Maximum Ratings (T _C =25 °C)			
Symbol	Parameter	Ratings	Unit
P _o	Input Optical Power	10	mW
V _{RD}	PD Reverse Voltage	20	V
I _{FD}	PD Forward Current	10	mA
T _{opr}	Operating Temperature	-40~+85	°C
T _{stg}	Storage Temperature	-40~+85	°C

