

GaAs-IR-Lumineszenzdiode
GaAs Infrared Emitter
Lead (Pb) Free Product - RoHS Compliant

SFH 4511



Wesentliche Merkmale

- GaAs-LED mit sehr hohem Wirkungsgrad
- 5mm Kunststoffgehäuse
- Peakwellenlänge 950 nm
- Sehr enger Abstrahlwinkel ($\pm 4^\circ$)
- Hohe Strahlstärke
- Hohe Zuverlässigkeit

Anwendungen

- IR-Fernsteuerung von Fernseh- und Rundfunkgeräten, Videorecordern, Lichtdimmern
- Gerätefernsteuerungen für Gleich- und Wechsellichtbetrieb
- Sensorik
- Diskrete Lichtschranken

Features

- Very highly efficient GaAs-LED
- 5mm plastic package
- Peak Wavelength 950 nm
- Very narrow radiation Angle (± 4 Deg.)
- High radiant intensity
- High reliability

Applications

- IR remote control of hi-fi and TV-sets, video tape recorders, dimmers
- Remote control for steady and varying intensity
- Sensor technology
- Discrete interrupters

Typ Type	Bestellnummer Ordering Code	Strahlstärkegruppierung¹⁾ ($I_F = 100$ mA, $t_p = 20$ ms) Radiant Intensity Grouping¹⁾ I_e (mW/sr)
SFH 4511	Q62703Q5557	> 63 (typ. 150)

¹⁾ gemessen bei einem Raumwinkel $\Omega = 0.001$ sr / measured at a solid angle of $\Omega = 0.001$ sr

Grenzwerte ($T_A = 25^\circ\text{C}$)**Maximum Ratings**

Bezeichnung Parameter	Symbol Symbol	Wert Value	Einheit Unit
Betriebs- und Lagertemperatur Operating and storage temperature range	$T_{\text{op}}, T_{\text{stg}}$	- 40 ... + 100	°C
Sperrspannung Reverse voltage	V_R	5	V
Durchlassstrom Forward current	I_F	100	mA
Stoßstrom, $t_p = 10 \mu\text{s}, D = 0$ Surge current	I_{FSM}	3	A
Verlustleistung Power dissipation	P_{tot}	165	mW
Wärmewiderstand Thermal resistance	R_{thJA}	450	K/W

Kennwerte ($T_A = 25^\circ\text{C}$)**Characteristics**

Bezeichnung Parameter	Symbol Symbol	Wert Value	Einheit Unit
Wellenlänge der Strahlung Wavelength at peak emission $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$	λ_{peak}	950	nm
Spektrale Bandbreite bei 50% von I_{max} Spectral bandwidth at 50% of I_{max} $I_F = 100 \text{ mA}$	$\Delta\lambda$	55	nm
Abstrahlwinkel Half angle	φ	± 4	Grad deg.
Aktive Chipfläche Active chip area	A	0.09	mm²
Abmessungen der aktiven Chipfläche Dimensions of the active chip area	$L \times B$ $L \times W$	0.3 × 0.3	mm
Schaltzeiten, I_e von 10% auf 90% und von 90% auf 10%, bei $I_F = 100 \text{ mA}, R_L = 50 \Omega$ Switching times, I_e from 10% to 90% and from 90% to 10%, $I_F = 100 \text{ mA}, R_L = 50 \Omega$	t_r, t_f	0.5	μs


Kennwerte ($T_A = 25^\circ\text{C}$)**Characteristics (cont'd)**

Bezeichnung Parameter	Symbol Symbol	Wert Value	Einheit Unit
Kapazität, Capacitance $V_R = 0 \text{ V}, f = 1 \text{ MHz}$	C_o	25	pF
Durchlassspannung Forward voltage $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$ $I_F = 1 \text{ A}, t_p = 100 \mu\text{s}$	V_F V_F	1.3 (≤ 1.5) 2.3 (≤ 2.8)	V V
Sperrstrom Reverse current $V_R = 5 \text{ V}$	I_R	0.01 (≤ 1)	μA
Gesamtstrahlungsfluss Total radiant flux $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$	Φ_e	22	mW
Strahlstärke Radiant intensity $I_F = 1 \text{ A}, t_p = 100 \mu\text{s}$	$I_e \text{ typ.}$	1200	mW/sr
Temperaturkoeffizient von I_e bzw. Φ_e , $I_F = 100 \text{ mA}$ Temperature coefficient of I_e or Φ_e , $I_F = 100 \text{ mA}$	TC_I	- 0.5	%/K
Temperaturkoeffizient von V_F , $I_F = 100 \text{ mA}$ Temperature coefficient of V_F , $I_F = 100 \text{ mA}$	TC_V	- 2	mV/K
Temperaturkoeffizient von λ , $I_F = 100 \text{ mA}$ Temperature coefficient of λ , $I_F = 100 \text{ mA}$	TC_λ	+ 0.3	nm/K

Strahlstärke I_e in Achsrichtunggemessen bei einem Raumwinkel $\Omega = 0.001 \text{ sr}$ **Grouping of Radiant Intensity I_e in Axial Direction**at a solid angle of $\Omega = 0.001 \text{ sr}$


Bezeichnung Parameter	Symbol	Wert Value	Einheit Unit
Strahlstärke Radiant intensity $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$	$I_e \text{ min.}$ $I_e \text{ typ.}$	63 150	mW/sr mW/sr
Strahlstärke Radiant intensity $I_F = 1 \text{ A},$ $t_p = 100 \mu\text{s}$	$I_e \text{ typ.}$	1200	mW/sr

Relative Spectral Emission
 $I_{\text{rel}} = f(\lambda)$




Forward Current

$I_F = f(V_F)$, single pulse, $t_p = 20 \mu\text{s}$




Permissible Pulse Handling Capability

$I_F = f(\tau)$, $T_A = 25^\circ\text{C}$
duty cycle $D = \text{parameter}$




Radiant Intensity $\frac{I_e}{I_e 100 \text{ mA}} = f(I_F)$

Single pulse, $t_p = 20 \mu\text{s}$




Max. Permissible Forward Current
 $I_F = f(T_A)$




Radiation Characteristics,

$I_{\text{rel}} = f(\phi)$



Maßzeichnung Package Outlines




Maße werden wie folgt angegeben: mm (inch) / Dimensions are specified as follows: mm (inch).

Package	5 mm radial (T 1 $\frac{3}{4}$)
Colour	black

Empfohlenes Lötpaddesign
Recommended Solder Pad

Wellenlöten (TTW)
TTW Soldering




OHLPY985

Maße werden wie folgt angegeben: mm (inch) / Dimensions are specified as follows: mm (inch).

Lötbedingungen
Soldering Conditions
Wellenlöten (TTW)
TTW Soldering

(nach CECC 00802)
 (acc. to CECC 00802)



Published by
 OSRAM Opto Semiconductors GmbH
 Wernerwerkstrasse 2, D-93049 Regensburg
www.osram-os.com

© All Rights Reserved.

The information describes the type of component and shall not be considered as assured characteristics.
 Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances. For information on the types in question please contact our Sales Organization.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Components used in life-support devices or systems must be expressly authorized for such purpose! Critical components¹, may only be used in life-support devices or systems² with the express written approval of OSRAM OS.

¹ A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or effectiveness of that device or system.

² Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or maintain and sustain human life. If they fail, it is reasonable to assume that the health of the user may be endangered.