


Specifications

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	126.92	127	127.08
Insertion Loss	dB	—	24.4	27
3 dB Bandwidth	MHz	6	6.03	—
18 dB Bandwidth	MHz	—	6.54	6.6
40 dB Bandwidth	MHz	—	6.8	7
50 dB Bandwidth	MHz	—	6.86	7.4
Passband Variation	dB	—	1.1	1.5
Absolute Delay	usec	—	3.685	4
Ultimate Rejection	dB	50	53	—
Material Temperature coefficient	KHz/°C	-2.286		
Ambient Temperature	°C	25		
Package Size	DIP2712 (27.0x12.8x4.7mm3)			

Notes:

1. All specifications are based on the test circuit shown
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. This is the optimum impedance in order to achieve the performance show

Matching Configuration



L1=22nH L2=33nH

Source /Load Impedance=50 ohm


Notes - Component values may change depending
on board layout.



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number	LBT12701		
Rev. Date	2005-9-23		
Rev.	1.0	Page	1/3

Package Dimension




Input:1
Output:5


	SIPAT Co., Ltd. (CETC No. 26 Research Institute) Nanping Huayuan Road No. 14 Chongqing, China, 400060		Part Number		LBT12701	
			Rev. Date		2005-9-23	
			Rev.		1.0	Page 2/3

Typical Performance


Frequency Response




Passband Response




Group Delay Variation($f_0 \pm 2.8\text{MHz}$)




Phase Linearity($f_0 \pm 2.8\text{MHz}$)



Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number	LBT12701	
Rev. Date	2005-9-23	
Rev.	1.0	Page 3/3