

TANTAMOUNT[®] Low ESR, Hi-Rel COTS, Built-In Fuse Conformal Coated


FEATURES

- High reliability; Weibull grading available
- Surge Current Testing per MIL-PRF-55365 options available
- Standard and Low ESR options
- Terminations: SnPb, Standard. 100 % Tin available
- Circuit protection for mission or safety critical systems
- Fuse characteristics: Guaranteed fuse protection at 9 A, 100 ms



PERFORMANCE/ELECTRICAL CHARACTERISTICS

Operating Temperature: - 55 °C to + 85 °C
(To + 125 °C with voltage derating)
Capacitance Range: 10 μF to 680 μF

Capacitance Tolerance: ± 20 %, ± 10 % standard
Voltage Rating: 4 WVDC to 50 WVDC

ORDERING INFORMATION								
T96	R	107	K	010	E	A	A	S
TYPE	CASE CODE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT + 85 °C	TERMINATION AND PACKAGING	RELIABILITY LEVEL	SURGE CURRENT	ESR
See Ratings and Case Codes Table.	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow.	K = ± 10 % M = ± 20 %	This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an "R" (6R3 = 6.3 V)	E: Sn/Pb Solder/7" (178 mm) reels L: Sn/Pb Solder/7" (178 mm) ½ reel C: 100 % Tin/7" (178 mm) reels H: 100 % Tin/7" (178 mm) ½ reel	A = 1.0 % Weibull B = 0.1 % Weibull (1) S = 40 h Burn-in Z = Non-Established Reliability	A = 10 cycles at +25 °C B = 10 cycles at -55 °C/+85 °C S = 3 cycles at +25 °C	S = Std L = Low	

Note: (1) Weibull 0.1 % may not be available on all ratings. See detailed notes in ratings table or contact marketing for availability

DIMENSIONS in inches [millimeters]


CASE CODE	L (MAX.)	W	H	A	B	D (REF.)	J (MAX.)
R	0.283 [7.2]	0.235 + 0.012/- 0.024 [6.0 + 0.3/- 0.6]	0.136 ± 0.012 [3.5 ± 0.3]	0.051 ± 0.012 [1.3 ± 0.30]	0.180 ± 0.024 [4.6 ± 0.6]	0.243 [6.2]	0.004 [0.1]

Note: The anode termination (D less B) will be a minimum of 0.010" (0.25 mm)

* Pb containing terminations are not RoHS compliant, exemptions may apply



RATINGS AND CASE CODES								
μF	4 V	6.3 V	10 V	16 V	20 V	25 V	35 V	50 V
10								R
15							R	R
22							R	R
33						R	R	
47					R			
68				R		R		
100			R		R	R		
120			R		R			
150			R		R			
180		R		R				
220		R	R	R				
330	R		R	R				
390		R						
680		R	R					

Note:

- All ratings are preliminary, contact marketing for availability

STANDARD/EXTENDED RATINGS						
CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. DC LEAKAGE AT + 25 °C (μA)	MAX. DF AT + 25 °C 120 Hz (%)	STD.(S) MAX. ESR AT + 25 °C 100 kHz (Ω)	(PRELIMINARY) LOW (L) MAX. ESR AT + 25 °C 100 kHz
4 WVDC AT + 85 °C, SURGE = 5.2 V . . . 2.7 WVDC AT + 125 °C, SURGE = 3.4 V						
330	R	T96R337(1)004(2)(3)(4)(5)	13.2	8	0.160	0.110
6.3 WVDC AT + 85 °C, SURGE = 8 V . . . 4 WVDC AT 125 °C, SURGE = 5 V						
180	R	T96R187(1)6R3(2)(3)(4)(5)	10.8	8	0.160	0.110
220	R	T96R227(1)6R3(2)(3)(4)(5)	13.2	8	0.160	0.110
390	R	T96R397(1)6R3(2)(3)(4)(5)	23.4	8	0.160	0.075
680	R	T96R687(1)6R3(2)(3)(4)(5)	40.8	12	0.120	0.075
10 WVDC AT + 85 °C, SURGE = 13 V . . . 7 WVDC AT 125 °C, SURGE = 8 V						
100	R	T96R107(1)010(2)(3)(4)(5)	10.0	8	0.170	0.105
120	R	T96R127(1)010(2)(3)(4)(5)	12.0	8	0.170	0.100
150	R	T96R157(1)010(2)(3)(4)(5)	15.0	8	0.160	0.095
220	R	T96R227(1)010(2)(3)(4)(5)	22.0	8	0.160	0.085
330	R	T96R337(1)010(2)(3)(4)(5)	33.0	8	0.160	0.085
680	R	T96R687(1)010(2)(3)(4)S	68.0	14	0.120	N/A
16 WVDC AT + 85 °C, SURGE = 20 V . . . 10 WVDC AT + 125 °C, SURGE = 12 V						
68	R	T96R686(1)016(2)(3)(4)(5)	10.9	6	0.630	0.125
180	R	T96R187(1)016(2)(3)(4)(5)	28.8	8	0.160	0.085
220	R	T96R227(1)016(2)(3)(4)(5)	35.2	8	0.150	0.085
330	R	T96R337(1)016(2)(3)(4)(5)	52.8	14	0.140	0.085
20 WVDC AT + 85 °C, SURGE = 26 V . . . 13 WVDC AT + 125 °C, SURGE = 16 V						
47	R	T96R476(1)020(2)(3)(4)(5)	9.4	6	0.230	0.140
100	R	T96R107(1)020(2)(3)(4)S	20.0	8	0.170	N/A
120	R	T96R127(1)020(2)(3)(4)(5)	24.0	8	0.170	0.110
150	R	T96R157(1)020(2)(3)(4)(5)	30.0	8	0.170	0.105

Notes:

- All ratings are preliminary, contact factory for availability
- (1) Capacitance Tolerance: K, M
- (2) Termination and Packaging: C, E, H, L
- (3) Reliability Level: A, B, S, Z
- (4) Surge Current: A, B, S
- (5) ESR: L, S



STANDARD/EXTENDED RATINGS						
25 WVDC AT + 85 °C, SURGE = 32 V . . . 17 WVDC AT + 125 °C, SURGE = 20 V						
33	R	T96R336(1)025(2)(3)(4)(5)	8.3	6	0.280	0.160
68	R	T96R686(1)025(2)(3)(4)(5)	17.0	6	0.230	0.125
100	R	T96R107(1)025(2)(3)(4)(5)	25	8	0.230	0.120
35 WVDC AT + 85 °C, SURGE = 46 V . . . 23 WVDC AT + 125 °C, SURGE = 28 V						
15	R	T96R156(1)035(2)(3)(4)(5)	5.3	6	0.410	0.220
22	R	T96R226(1)035(2)(3)(4)(5)	7.7	6	0.310	0.270
33	R	T96R336(1)035(2)(3)(4)(5)	11.6	6	0.310	0.230
50 WVDC AT + 85 °C, SURGE = 65 V . . . 33 WVDC AT + 125 °C, SURGE = 40 V						
10	R	T96R106(1)050(2)(3)(4)(5)	5.0	6	0.680	0.530
15	R	T96R156(1)050(2)(3)(4)(5)	7.5	6	0.430	0.380
22	R	T96R226(1)050(2)(3)(4)(5)	11.0	6	0.420	0.330

Notes:

- All ratings are preliminary, contact factory for availability
- (1) Capacitance Tolerance: K, M
- (2) Termination and Packaging: C, E, H, L
- (3) Reliability Level: A, B, S, Z
- (4) Surge Current: A, B, S
- (5) ESR: L, S



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.