

MOS Field Effect Transistor

2SK1587


■ Features

- Directly driven by Ics having a 3V power supply.

- Has low on-state resistance

$R_{DS(on)}=0.8\ \Omega\ \text{MAX.}@V_{GS}=2.5V, I_D=0.5A$

$R_{DS(on)}=0.5\ \Omega\ \text{MAX.}@V_{GS}=4.0V, I_D=1.0A$



■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Rating | Unit |
|-------------------------|-----------|-------------|------------------|
| Drain to source voltage | V_{DS} | 16 | V |
| Gate to source voltage | V_{GS} | ± 16 | V |
| Drain current (DC) | I_D | ± 2.0 | A |
| Drain current(pulse) * | I_D | ± 4.0 | A |
| Power dissipation | P_D | 2.0 | W |
| Channel temperature | T_{ch} | 150 | $^\circ\text{C}$ |
| Storage temperature | T_{stg} | -55 to +150 | $^\circ\text{C}$ |

* $PW \leq 10\text{ms}$, duty cycle $\leq 5\%$

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Testconditions | Min | Typ | Max | Unit |
|-------------------------------------|---------------|-------------------------------------------------------------------------|-----|-----|-----------|---------------|
| Drain cut-off current | I_{DSS} | $V_{DS}=16V, V_{GS}=0$ | | | 10 | μA |
| Gate leakage current | I_{GSS} | $V_{GS}=\pm 16V, V_{DS}=0$ | | | ± 5.0 | μA |
| Gate to source cutoff voltage | $V_{GS(off)}$ | $V_{DS}=10V, I_D=1\text{mA}$ | 0.8 | 1.2 | 1.6 | V |
| Forward transfer admittance | $ Y_{fs} $ | $V_{DS}=5.0V, I_D=1.0A$ | 0.4 | | | s |
| Drain to source on-state resistance | $R_{DS(on)}$ | $V_{GS}=2.5V, I_D=0.5A$ | | 0.5 | 0.8 | Ω |
| | | $V_{GS}=4.0V, I_D=1.0A$ | | 0.3 | 0.5 | Ω |
| Input capacitance | C_{iss} | $V_{DS}=5.0V, V_{GS}=0, f=1\text{MHz}$ | | 180 | | pF |
| Output capacitance | C_{oss} | | | 160 | | pF |
| Reverse transfer capacitance | C_{rss} | | | 55 | | pF |
| Turn-on delay time | $t_{d(on)}$ | | | | 100 | |
| Rise time | t_r | $I_D=1.0A, V_{GS(on)}=3.0V, R_L=10\ \Omega, V_{DD}=10V, R_G=10\ \Omega$ | | 700 | | ns |
| Turn-off delay time | $t_{d(off)}$ | | | 150 | | ns |
| Fall time | t_f | | | 200 | | ns |

■ Marking

| Marking | NF |
|---------|----|
| | |