

# HPL, TFL series, high-precision, thin-film chip inductors.



These 0805, 0402 and 0201 chip inductors are adjustment free due to their tight tolerance. Additionally, this part also offers a high self-resonance frequency of 1 GHz and high Q value and a very excellent rated current.


RoHS compliant

Completely lead free



## SPECIFICATIONS

### Mechanical



| Dimension (Inch Size) | HPL0603 (0201) | HPL1005 TFL0510 <sup>(0402)</sup> | TFL0816 (0603) |
|-----------------------|----------------|-----------------------------------|----------------|
| L                     | 0.60±0.05      | 1.00±0.10                         | 1.60±0.10      |
| W                     | 0.30±0.05      | 0.50±0.10                         | 0.80±0.10      |
| P                     | 0.07±0.05      | 0.15±0.10                         | 0.30±0.20      |
| T                     | 0.28±0.05      | 0.40±0.10                         | 0.45±0.10      |

(unit : mm)

### Electrical

| Type                          | HPL0603        |          | HPL1005        |          |
|-------------------------------|----------------|----------|----------------|----------|
| inductance value              | E-24           |          | E-24           |          |
| inductance range (nH)         | 1.0~5.6        | 6.2~27   | 1.0~9.1        | 10~39    |
| inductance tolerance          | ±0.1nH, ±0.2nH | ±2%      | ±0.1nH, ±0.2nH | ±2%      |
| Q value (at 300MHz)           | 10             | 8~10     | 20~15          | 15~13    |
| Q value (at 800MHz) typ.      | 14~17          | 14~16    | 35~25          | 25~20    |
| Q value (at 1.5GHz) typ.      | 18~25          | 18~20    | 50~30          | 30~25    |
| Self resonance Frequency(GHz) | 10~6.0         | 3.5      | 7.0~4.0        | 3.5      |
| DC resistance(Ω)              | 0.1~0.8        | 0.8~1.5  | 0.01~0.4       | 0.5~0.8  |
| Rated Current(A)              | 0.5~0.2        | 0.2~0.15 | 1.8~0.34       | 0.3~0.24 |
| Package                       | 10,000pcs/reel |          |                |          |

Measured at 500MHz in case of HPL0603, at 300MHz in case of HPL1005

| Type                          | TFL0510        |           |           |           |           |           | TFL0816       |         |         |          |          |
|-------------------------------|----------------|-----------|-----------|-----------|-----------|-----------|---------------|---------|---------|----------|----------|
| inductance value              | E-24           |           |           |           |           |           | E-12          |         |         |          |          |
| inductance range (nH)         | 1.0~1.2        | 1.3~2.2   | 2.4~3.9   | 4.3~9.1   | 10~16     | 18~39     | 1.0~4.7       | 5.6~8.2 | 10~27   | 33~68    | 82~100   |
| inductance tolerance          | ±0.1nH, ±0.2nH |           | ±0.2nH    |           | ±2%       | ±3%       | ±0.2nH        |         | ±2%     | ±2%      |          |
| Q value (at 300MHz)           | 10             |           |           | *10       |           |           | 20            | 15      | 15      | *15      | *10      |
| Q value (at 800MHz) typ.      | 21             |           |           |           |           |           | 34~30         |         | 30~25   | 25       | 15       |
| Q value (at 1.5GHz) typ.      | 25             |           | 25~20     | 20        | **20      | 38~35     |               | 35~30   | **      |          |          |
| Self resonance Frequency(GHz) | 7.0            |           | 5.5~4.0   | 4.0       | 2.0~1.5   | 6.0~5.0   | 5.0~4.0       | 4.0~2.0 | 1.5~1.0 | 1.0      |          |
| DC resistance(Ω)              | 0.1            | 0.15~0.20 | 0.20~0.40 | 0.60~1.50 | 1.50~2.55 | 2.55~4.00 | 0.10~0.25     | 0.50    | 1.0~2.0 | 2.0~4.5  | 6.0~8.5  |
| Rated Current(A)              | 1.2            | 0.93~0.60 | 0.58~0.42 | 0.34~0.21 | 0.21~0.16 | 0.16~0.12 | 1.0~0.6       | 0.40    | 0.3~0.2 | 0.2~0.14 | 0.12~0.1 |
| Package                       | 10,000pcs/reel |           |           |           |           |           | 5,000pcs/reel |         |         |          |          |

\* Measured at 200MHz in case of 33,36,39nH(TFL0510) and 33-100nH(TFL0816)

\*\* No measuring in case of 33,36,39nH(TFL0510) and 33-100nH(TFL0816)



## PART NUMBER

### HPL 0603 - 1N0 (-E02)

