



MODEL SPECIFICATIONS

MECHANICAL

MODEL NUMBER(S): 51-331DA-XX*F-XX*R-6-6
 51-332DA-XX*F-XX*R-6-6
 *SUBSTITUTE WITH DESIRED COUPLING VALUE

MATERIAL: 6061/T-6 ALUM.
 BODY: STAINLESS STEEL
 CONNECTORS: STEEL EPOXY COATING
 FINISH: UNIQUE CORROSION RESISTANT 316 STAINLESS
 FLANGES: 51 COVER IS STANDARD., EQUIV. TO MIL-F-3922/70-024

| | | | | | | | |
|---|-----------|-----------|-----------|---|-----------------|------------------|--------------|
| MATERIAL | SEE NOTES | TREATMENT | - | DRAWN | R. LYNCH | DATE | 4/14/05 |
| FINISH | SEE NOTES | MOD. NO. | SEE NOTES | CHECKED | | DATE | |
| OUTLINE, WR51 DUAL COUPLER, SHORT LENGTH HIGH DIRECTIVITY | | | | APPROVED | | DATE | |
| | | | | CAGE CODE: OR8N4 | | DO NOT SCALE DWG | |
| ADVANCED TECHNICAL MATERIALS, INC. 49 RIDER AVE., PATCHOGUE N.Y. 11772 TEL: (631) 289-0363 FAX: (631) 289-0358 http://www.atmmicrowave.com | | | | UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES | FRACTIONS ±1/64 | DECIMALS ±.03 | ANGLES ±1/2° |
| PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT THE PRIOR WRITTEN CONSENT OF ATM, INC. | | | | TOLERANCES ARE: | | | SHEET. 1/1 |
| | | | | SCALE | NONE | DWG. NO. | 7191W |
| | | | | | | REV. | - |