

VCO Product Specification

 Model:
 VCO790-2965K(Y)
 Rev:
 Date:
 8/31/2006

 Customer:
 SIRENZA MICRODEVICES

Operating Temperature Range: (-40 ° to 85 ° C)

PB RoHS Compliant

To order models as RoHS Compliant add "Y" suffix to base model number.

Parameter	Min	Turn	Max	Units	x	Remarks
	Min	Тур	Мах			Remarks
Frequency Range -	2865		3065	MHz	Х	
Tuning Voltage:						
2865 MHz	0.8	1.3		Vdc	Х	
3065 MHz		2.4	3.5	Vdc	Х	
Tuning Sensitivity -	140		200	MHz/V	Х	
Output Power -	4	6	10	dBm	Х	
Output Phase Noise:						
10 kHz		-89	-75	dBc/Hz		
100 kHz		-111	-95	dBc/Hz	Х	
Power Supply -	3.9	4.1	4.3	Volts		
Supply Current -		26	32	mA	Х	Vcc=4.1V
Harmonic Suppression:						
2nd Harmonic		-20	-10	dBc	Х	
Spurious (Non-Harmonic) -			-50	dBc		
Frequency Pushing - 3.9 - 4.3 V		3	25	MHz p-p		
Frequency Pulling - 12 dB RL		27	34	MHz p-p		
Tuning Port Capacitance -		10		pF		

Package Information

Package Type: K (0.3 x 0.3 x 0.079 inches)	Drawing Number:	60879
--	-----------------	-------

Comments

 \boldsymbol{X} Indicates parameter to be tested 100% in production

X INDICATES PARAMETER TO BE TESTED 100% IN PRODUCTION

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices and/or systems.

Page 1 of 1

Sirenza Microdevices, Inc.

tel 303.327.3030