

Silicon NPN Power Transistors

2SC1195

DESCRIPTION


- With TO-3 package
- High power dissipation
- Low collector saturation voltage

APPLICATIONS

- For line operated audio output amplifier and switching power supply drivers applications

PINNING(see Fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector



Absolute maximum ratings(Ta=?)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	200	V
V_{CEO}	Collector-emitter voltage	Open base	200	V
V_{EBO}	Emitter-base voltage	Open collector	5	V
I_C	Collector current		2.5	A
P_C	Collector power dissipation	$T_C=25^\circ$	100	W
T_j	Junction temperature		150	°
T_{stg}	Storage temperature		-55~150	°

Silicon NPN Power Transistors

2SC1195

CHARACTERISTICS

T_j=25° unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =30mA ; I _B =0	200			V
V _{(BR)CBO}	Collector-base breakdown voltage	I _C =1mA ; I _E =0	200			V
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =1mA ; I _C =0	5			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =2.5A ; I _B =0.5A			1.5	V
V _{BE}	Base-emitter on voltage	I _C =1A ; V _{CE} =5V			1.5	V
I _{CBO}	Collector cut-off current	V _{CB} =200V ; I _E =0			0.1	mA
I _{EBO}	Emitter cut-off current	V _{EB} =5V ; I _C =0			0.1	mA
h _{FE}	DC current gain	I _C =1A ; V _{CE} =5V	30		150	

Silicon NPN Power Transistors

2SC1195

PACKAGE OUTLINE




Fig.2 outline dimensions (unindicated tolerance:±0.1mm)