


RoHS Compliant Product


A suffix of "-C" specifies halogen & lead-free

FEATURES


- Low forward voltage
- Fast switching




SOT-23		
Dim	Min	Max
A	2.800	3.040
B	1.200	1.400
C	0.890	1.110
D	0.370	0.500
G	1.780	2.040
H	0.013	0.100
J	0.085	0.177
K	0.450	0.600
L	0.890	1.020
S	2.100	2.500
V	0.450	0.600
All Dimension in mm		




CMPSH-3
Marking: D95



CMPSH-3A
Marking: DB1



CMPSH-3C
Marking: DB2



CMPSH-3S
Marking: DA5

MAXIMUM RATINGS @ $T_A = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Limits	Unit
Peak Repetitive Peak Reverse Voltage	V_{RRM}	30	V
Working peak Reverse Voltage	V_{RWM}		
DC Blocking Voltage	V_R		
Forward Continuous Current	I_{FM}	100	mA
Power Dissipation	P_D	350	mW
Thermal Resistance	$R_{\theta JA}$	357	$^\circ\text{C/W}$
Junction and Storage Temperature	T_J, T_{STG}	150, -55 ~ 150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min	Max	Unit
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R = 100\text{ }\mu\text{A}$		30	V
Reverse Voltage Leakage Current	I_R	$V_R = 25\text{ V}, T_A = 25\text{ }^\circ\text{C}$		500	nA
		$V_R = 25\text{ V}, T_A = 100\text{ }^\circ\text{C}$		100	μA
Forward Voltage	V_F	$I_F = 2\text{ mA}$		0.33	V
		$I_F = 15\text{ mA}$		0.45	
		$I_F = 100\text{ mA}$		1	
Diode Capacitance	C_{tot}	$V_R = 1\text{ V}, f = 1\text{ MHz}$	7		pF
Junction and Storage Temperature	t_{ff}	$I_F = I_R = 10\text{ mA}$ $I_{RR} = 1\text{ mA}, R_L = 100\Omega$		5	Ns

ELECTRICAL CHARACTERISTICS CURVES

