## PDG-02A Series 0° POWER DIVIDERS / COMBINERS

10 to 1000 MHz / 2-Way / Broadband / Minimal Size and Weight / Low 0.2" Profile / Surface Mount



		PRINCIPAL SPECIFICATIONS									
Model	Frequency Range, MHz	lsolation, dB,		Insertion Loss, dB,		Amplitude Balance, dB,		Phase Balance,		VSWR	
Number		Min.	Тур.	Max.	Тур.	Max.	Тур.	Max.	Тур.	Max.	Тур.
PDG-02A-250	10 - 500	20	25	1.0	0.5	0.2	0.1	2°	1°	1.5:1	1.3:1
PDG-02A-500	50 - 1000	18	25	1.5	1.0	0.3	0.2	4°	2°	1.5:1	1.3:1

## **General Notes:**


1. The basic power divider is a hybrid junction with one of its ports internally terminated. For in-phase power division, such as provided in the PDG-02A series, the E port is internally terminated.

2. Careful design and construction insure phase and amplitude uniformity between units. Additionally, these units provide excellent transfer phase linearity and amplitude flatness. These characteristics are of critical importance to the successful design of modern multi-channel receivers, transmitters and antenna systems.

3. Merrimac Power Dividers/Combiners are available in a variety of packages to suit most requirements. The surface mounted versions in the PDG-02A series use lumped element design. This approach is particularly appropriate for those applications where small size is important.

## GENERAL SPECIFICATIONS

Impedance:	50 $\Omega$ nom.					
Coupling (Theoretical):	– 3.0 dB					
CW Input Power: 250 mW max. (When used as divider with 1.2:1 VSWR <sub>out</sub> ) Internal Load Dissipation: 28 mW max.						
Weight, nominal:	0.02 oz. (0.5 g)					
Operating Temperature:	– 55° to + 85°C					



For further information contact MERRIMAC/41 Fairfield PI., West Caldwell, NJ, 07006/973-575-1300/FAX 973-575-0531