

Single N-channel MOSFET

ELM17408GA-S

General description

ELM17408GA-S uses advanced trench technology to provide excellent $R_{ds(on)}$, low gate charge and operation with gate voltages as low as 1.8V.

Features

- $V_{ds}=20V$
- $I_d=2.2A$ ($V_{gs}=4.5V$)
- $R_{ds(on)} < 82m\Omega$ ($V_{gs}=4.5V$)
- $R_{ds(on)} < 95m\Omega$ ($V_{gs}=2.5V$)
- $R_{ds(on)} < 120m\Omega$ ($V_{gs}=1.8V$)

Maximum absolute ratings


Parameter		Symbol	Limit	Unit	Note
Drain-source voltage		V_{ds}	20	V	
Gate-source voltage		V_{gs}	± 8	V	
Continuous drain current	$T_a=25^{\circ}C$	I_d	2.20	A	1
	$T_a=70^{\circ}C$		1.75		
Pulsed drain current		I_{dm}	10	A	2
Power dissipation	$T_a=25^{\circ}C$	P_d	0.625	W	1
	$T_a=70^{\circ}C$		0.400		
Junction and storage temperature range		T_j, T_{stg}	-55 to 150	$^{\circ}C$	

Thermal characteristics

Parameter		Symbol	Typ.	Max.	Unit	Note
Maximum junction-to-ambient	$t \leq 10s$	$R\theta_{ja}$	160	200	$^{\circ}C/W$	1
Maximum junction-to-ambient	Steady-state		180	220	$^{\circ}C/W$	
Maximum junction-to-lead	Steady-state	$R\theta_{jl}$	130	160	$^{\circ}C/W$	3


Pin configuration

SC-70-6 (TOP VIEW)



Pin No.	Pin name
1	DRAIN
2	DRAIN
3	GATE
4	SOURCE
5	DRAIN
6	DRAIN

Circuit



Single N-channel MOSFET

ELM17408GA-S

Electrical characteristics

Ta=25°C

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
STATIC PARAMETERS						
Drain-source breakdown voltage	BV _{dss}	I _d =250 μ A, V _{gs} =0V	20			V
Zero gate voltage drain current	I _{dss}	V _{ds} =16V V _{gs} =0V			1	μ A
		T _j =55°C			5	
Gate-body leakage current	I _{gss}	V _{ds} =0V, V _{gs} = $\pm$ 8V			100	nA
Gate threshold voltage	V _{gs(th)}	V _{ds} =V _{gs} , I _d =250 μ A	0.4	0.6	0.8	V
On state drain current	I _{d(on)}	V _{gs} =4.5V, V _{ds} =5V	10			A
Static drain-source on-resistance	R _{ds(on)}	V _{gs} =4.5V I _d =2.2A		67	82	m Ω
		T _j =125°C		99	125	
		V _{gs} =2.5V, I _d =2A		78	95	m Ω
		V _{gs} =1.8V, I _d =1A		96	120	m Ω
Forward transconductance	G _{fs}	V _{ds} =5V, I _d =1.6A		6.7		S
Diode forward voltage	V _{sd}	I _s =1A, V _{gs} =0V		0.69	1.00	V
Max. body-diode continuous current	I _s				0.91	A
DYNAMIC PARAMETERS						
Input capacitance	C _{iss}	V _{gs} =0V, V _{ds} =10V, f=1MHz		499		pF
Output capacitance	C _{oss}			65		pF
Reverse transfer capacitance	C _{rss}			56		pF
Gate resistance	R _g	V _{gs} =0V, V _{ds} =0V, f=1MHz		3		Ω
SWITCHING PARAMETERS						
Total gate charge	Q _g	V _{gs} =4.5V, V _{ds} =10V, I _d =2.2A		6.02		nC
Gate-source charge	Q _{gs}			0.41		nC
Gate-drain charge	Q _{gd}			1.35		nC
Turn-on delay time	t _{d(on)}	V _{gs} =5V, V _{ds} =10V R _l =4.5 Ω , R _{gen} =6 Ω		6.5		ns
Turn-on rise time	t _r			8.0		ns
Turn-off delay time	t _{d(off)}			61.0		ns
Turn-off fall time	t _f			16.0		ns
Body diode reverse recovery time	t _{rr}	I _f =2.2A, dI/dt=100A/ μ s		23.2		ns
Body diode reverse recovery charge	Q _{rr}	I _f =2.2A, dI/dt=100A/ μ s		8.6		nC

NOTE :

1. The value of R θ _{ja} is measured with the device mounted on 1in² FR-4 board of 2oz. Copper, in still air environment with Ta=25°C. The value in any given applications depends on the user's specific board design, The current rating is based on the t $\leq$ 10s thermal resistance rating.
2. Repetitive rating, pulse width limited by junction temperature.
3. The R θ _{ja} is the sum of the thermal impedance from junction to lead R θ _{jl} and lead to ambient.
4. The static characteristics in Figures 1 to 6 are obtained using 80 μ s pulses, duty cycle 0.5%max.
5. These tests are performed with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with Ta=25°C. The SOA curve provides a single pulse rating.

Single N-channel MOSFET

ELM17408GA-S

Typical electrical and thermal characteristics




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

Single N-channel MOSFET

ELM17408GA-S




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance