FEATURES AND SPECIFICATIONS

Features and Benefits

- Hand-held tool with 360° swivel head that permits use in confined areas
- Crimps a wide range of terminals for production flexibility
- External pressure adjustment allows operator to changes settings easily
- Insulated fiberglass handles reduce shock hazard
- Steel carrying case included to prevent damage to the tool



Weight: 5.22kg (11.5lb)

Size: Width -432mm (17.0")

Height -559mm (22.0")



nolex[®] Application Tooling

19286-0107

DLHH Manual Crimp Hand Tool Dieless



ORDERING INFORMATION

Order No.	Wire Gauge (AWG)	Pressure Setting
19286-0107	8	3.0
19286-0107	6	3.5
19286-0107	4	4.0
19286-0107	2	4.5
19286-0107	1	6.0
19286-0107	1/0	6.0
19286-0107	2/0	6.5
19286-0107	3/0	7.0
19286-0107	4/0	7.0



Bringing People & Technology Together, WorldwideSM

Americas Headquarters Lisle, Illinois 60532 U.S.A. 1-800-78M0LEX amerinfo@molex.com Far East North Headquarters Yamato, Kanagawa, Japan 81-462-65-2324 feninfo@molex.com Far East South Headquarters Jurong, Singapore 65-6-268-6868 fesinfo@molex.com Visit our website at www.molex.com European Headquarters Munich, Germany 49-89-413092-0 eurinfo@molex.com Corporate Headquarters 2222 Wellington Ct. Lisle, IL 60532 U.S.A. 630-969-4550 Fax:630-969-1352