



Schematic:



Electrical Specifications: 25°C

TURNS RATIO: TX 1CT:1CT $\pm$ 3%, RX 1CT:1CT $\pm$ 3%
 Isolation Voltage: 1500 Vrms (INPUT to OUTPUT)
 UTP SIDE OCL: 350uH Min @100KHz 100mV 8mADC
 Rise Time (10–90%): 2.5ns Typical
 Insertion Loss (1–100MHz): –1.0dB Maximum
 Insertion Loss (100MHz–125MHz): –1.5dB Typ.
 Return Loss: –20dB Typ. @30MHz
 –12dB Typ @80MHz
 Crosstalk 32MHz: 40.0dB Min
 62MHz: 35.0dB Min
 100MHz: 30.0dB Min
 CMRR 100KHz–100MHz: 35.0dB Typ

Note:

1. Solderability: Leads shall meet MIL–STD–202, Method 208D for solderability.
2. Flammability: UL94V–0,
3. ASTM oxygen index: > 28% ,
4. Temperature rating: 155°C. UL file E151556,
5. Operating Temperature Range: All listed parameters are to be within tolerance from –40°C to +85°C


DOC. REV. A/1

PROPRIETARY:

Document is the property of XFMRs Group & is not allowed to be duplicated without authorization

XFMRs Inc.		Title: 2x6 STACKED COMBO SERIES	
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx $\pm$ 0.010 Dimensions in Inch	P/N: XFATM8J–STACK12–4		REV. A
	DWN.	李小锋	Mar–24–04
	CHK.	廖玉坤	Mar–24–04
	APP.	BW	Mar–24–04
SHEET 1 OF 2			

Mechanical Dimensions:



SUGGESTED MOUNTING PATTERN (COMPONENT SIDE)

DOC. REV. A/1

XFMRs Inc.

Title: Mechanical Dimensions
For 2x6 STACKED COMBO Series

UNLESS OTHERWISE SPECIFIED
TOLERANCES:

P/N: XFATM8J-STACK12-4

REV. A

.xxx ± 0.010

DWN.

廖玉坤

Mar-24-04

Dimensions in Inch

CHK.

李清儿

Mar-24-04

SHEET 2 OF 2

APP.

BW

Mar-24-04

PROPRIETARY:

Document is the property of XFMRs Group & is not allowed to be duplicated without authorization.