


Device	400TO220	UV-LED
Dice Material	GaN	
Light Color	UV	

Package Dimensions:



Absolute Maximum Ratings at Ta = 25°C

Parameter	Max.	Unit
DC Forward Current	20	mA
Operation Temperature	Topr: -25 ~ +85	°C
Storage temperature	Topr: -25 ~ +100	°C
Reverse Voltage	5	V
Lead Soldering Temperature [1.6mm From Body] 260°C for 3 seconds		

Electrical Optical Characteristics at Ta = 25°C

Description	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Spectral Line Half-Width	$\Delta\lambda$	-	5	-	nm	If = 20 mA
Forward Voltage	Vf	-	3.8	-	V	If = 20 mA
Reverse Current	Ir	-	-	10	μ A	Vr = 5 V
Peak Emission Wavelength	λ_p	390	395	400	nm	If = 20 mA
Viewing Angle	2 $\theta_{1/2}$	-	60	-	°	If = 20 mA
Optical Power	Po	2.5	3.5	4.5	mW	If = 20 mA

Notes:

1. Soldering shall be performed after lead forming.
2. All dimensions are in millimeters.
3. Static electricity damages the LEDs. It is recommended to take full care when handling products.

ROITHNER LASERTECHNIK
A-1040 Vienna, Austria
Schönbrunner Straße 7
Tel.: +43-1-586 52 43 - 0
Fax.: +43-1-586 52 43 44
e-mail: office@roithner-laser.com
http://www.roithner-laser.com