



AC-Capacitors, RC Networks (Spark Quenching Capacitors) Class X2 AC 250V (MKT)

Dimensions in mm



CIRCUIT DIAGRAM:



FEATURES:

Product is completely lead (Pb)-free
Product is RoHS compliant



RoHS
COMPLIANT

TECHNICAL DATA:

See page 21 (Document Number 26504)

TERMINALS:

Standard: radial tinned copper wire. On request: insulated stranded copper wire, type LiY 0.5mm² (or AWG 20) ends stripped and tinned or insulated solid copper wire, type YV (d = 0.8mm) with stripped ends

RATED VOLTAGE:

AC 250V, 50/60Hz

COATING:

Plastic case, epoxy resin sealed, flame retardant
UL 94V-0

RESISTOR:

P₄₀ = 0.75 Watts
Value variation according to row E 12 of DIN IEC 63
See page 14 (Document Number 26537)

APPROVAL

COUNTRY		SPECIFICATION	APPROVAL REFERENCE	APPROVAL MARK
U.S.A.	UL	UL 1283	E 76297	

CAPACITANCE	TOL. (%)	RESISTOR VALUE (Ω)	PITCH (mm)	BOX NO	DIMENSIONS W x H x L (mm) (+ 0.2/- 0.4mm)	WEIGHT (LEAD LENGTH ≤ 6 ⁻¹ mm) (g)	QUANTITY PACKAGE (LEAD LENGTH ≤ 6 ⁻¹ mm) (pcs)*	ORDERING CODE**
0.068 μFX2	± 20	2.2 - 470	22.5	12	8.3 x 16.3 x 26.3	5.3	200	F1776-368-... / ...Ω
0.1 μFX2	± 20	2.2 - 470	22.5	12	8.3 x 16.3 x 26.3	5.3	200	F1776-410-... / ...Ω
0.15 μFX2	± 20	2.2 - 470	22.5	13	10.3 x 18.3 x 26.3	7.0	150	F1776-415-... / ...Ω
0.22 μFX2	± 20	2.2 - 470	27.5	14	11.0 x 20.3 x 31.3	10.0	125	F1776-422-... / ...Ω
0.27 μFX2	± 20	2.2 - 390	27.5	14	11.0 x 20.3 x 31.3	10.0	125	F1776-427-... / ...Ω
0.33 μFX2	± 20	2.2 - 220	27.5	14	11.0 x 20.3 x 31.3	10.0	125	F1776-433-... / ...Ω
0.47 μFX2	± 20	2.2 - 220	27.5	15	13.0 x 23.3 x 31.3	13.1	110	F1776-447-... / ...Ω
0.68 μFX2	± 20	2.2 - 100	37.5	16	14.0 x 24.3 x 41.3	21.3	80	F1776-468-... / ...Ω

* Further information about packaging quantities with different lead length and/or taped versions. See page 16 (Document No 27608 Packaging Quantities). Use Box No. as reference

** Ordering Code: For RC-network 0.068 μF + 100Ω: F1776-368-... / ...Ω.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.