

# IPPC-6152A

## 15" XGA TFT LCD Pentium® M/Celeron® M Industrial Panel PC with 2 x PCI Slots



### Features

- 15" XGA TFT LCD with touchscreen
- Intel® Pentium® M processor up to 2.0 GHz/Celeron® M 1.5 GHz
- System memory supports dual channel DDR2 SDRAM up to 2 GB
- Offers two expansion slots for PCI add-on cards
- Dual Lan, supports one Gigabit Lan
- Front USB access and system reset function
- Flat-sealed front panel
- Control box with gull-wing design for easy installation and maintenance
- Front panel is NEMA4/IP65 compliant

### Introduction

The IPPC-6152A is an Industrial Panel PC with front USB access, supports Pentium M/Celeron M processor up to 2 GHz, DDR2 memory bus support up to 2 GB, slim CD-ROM driver, two expansion PCI slots. The flat-sealed front panel design allows easier cleaning and liquid run off. Also the control box has the gull-wing design for easy components installation and maintenance.

### Specifications

#### General

- **BIOS** Award® 512KB Flash BIOS
- **Certifications** UL, CE, FCC, CCC, BSMI
- **Enclosure** Die-cast flat-sealed front with SGCC Housing
- **Dimension (W x H x D)** 449.92 x 315.63 x 141.7 mm (17.73" x 12.44" x 5.58")
- **Mounting** Panel, Rack (option)
- **OS Support** Windows 2000, XP Professional
- **Power Input** 100 - 240 Vac @ 50 - 60 Hz, 4 - 2 A
- **Power Output** +3.3 V @ 16.8 A, +5 V @ 12 A, +12 V @ 10 A, +5 Vsb @ 2 A, -12 V @ 0.8 A
- **Power Supply** 180 W, MTBF: 100,000 hrs
- **Weight (Gross)** 10 Kg (22.04 lbs)

#### System Hardware

- **CPU** Supports Socket 478 based Intel Pentium M up to 2.0 GHz/Celeron M 1.5 GHz
- **Chipset** Intel 915GME
- **Memory** Up to 2 GB DDR2 240pin SDRAM 400/533 MHz
- **LAN** 10/100Base-T Ethernet x 1, 10/100/1000Base-T Ethernet x 1
- **Expansion** 2 x half-length PCI Slots
- **Storage** 1 x SATA HDD interface (2.5" HDD bay)
- **Optical Driver** 1 x Slim Type DVD/CDRW
- **I/Os** 1 x RS-232  
5 x USB 2.0 (one at front)  
2 x PS2 (Keyboard, Mouse)  
1 x VGA Port  
1 x Parallel Port  
Mic-in, Line-in, Line-out

#### LCD Display

- **Backlight Life** 50,000 hrs
- **Contrast Ratio** 500 : 1
- **Display Size** 15"
- **Display Type** XGA TFT LCD
- **Luminance** 250 cd/m<sup>2</sup>
- **Max. Colors** 16.2 M (RGB 6-bit + FRC data)
- **Max. Resolution** 1024 x 768
- **Viewing Angle (H/V°)** 140/120

#### Touchscreen (Optional)

- **Lifespan** 10 millions times touch at single point
- **Light Transmission** > 80%
- **Type** Analog resistive 8-wire

#### Environment


- **Humidity** 5 - 85% @ 40 °C (non-condensing)
- **Ingress Protection** Front panel: NEMA4/IP65
- **Operating Temperature** 0 - 50° C (32 ~ 122° F)
- **Storage Temperature** -20 - 60° C (-4 ~ 140° F)
- **Vibration Protection** 5 - 500 Hz, 1 Grms random vibration

### Ordering Information

- **IPPC-6152A-X0AE** 15" Ind. Panel PC, Pentium M/Celeron M, 2 x PCI
- **IPPC-6152A-R0AE** 15" Ind Panel PC, Pentium M/Celeron M, 2xPCI, TS

## Dimensions

Unit: mm




**Panel Cut-out Dimensions: 428 x 297 mm**

## Accessories

- **IPPC-6152A-RMKE** IPPC-6152A/IPPC-6152F Rack mount kit
- **1702002600** Power Cable US Plug 1.8 M
- **1702002605** Power Cable EU Plug 1.8 M
- **1702031801** Power Cable UK Plug 1.8 M
- **1702031836** Power Cable China/Australia Plug 1.8 M

## Front Accessible USB Port



## I/O View

