


LL4148

SILICON EPITAXIAL PLANAR DIODE

fast switching diode in MiniMELF case especially suited for automatic surface mounting




Glass case MiniMELF
Dimensions in mm

Absolute Maximum Ratings ($T_a = 25\text{ }^\circ\text{C}$)

| Parameter | Symbol | Value | Unit |
|---|-------------------------------|-------------------|------------------|
| Peak Reverse Voltage | V_{RM} | 100 | V |
| Reverse Voltage | V_R | 75 | V |
| Average Rectified Forward Current | $I_{F(AV)}$ | 200 | mA |
| Non-repetitive Peak Forward Surge Current | at $t = 1\text{ s}$ | 0.5 | A |
| | at $t = 1\text{ ms}$ | 1 | |
| | at $t = 1\text{ }\mu\text{s}$ | 4 | |
| Power Dissipation | P_{tot} | 500 ¹⁾ | mW |
| Junction Temperature | T_j | 175 | $^\circ\text{C}$ |
| Storage Temperature Range | T_s | - 65 to + 175 | $^\circ\text{C}$ |

¹⁾ Valid provided that electrodes are kept at ambient temperature.



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 7116




ISO 9001:2000
Certificate No. 0506098

Dated : 15/09/2007


Characteristics at $T_j = 25\text{ }^\circ\text{C}$

| Parameter | Symbol | Min. | Max. | Unit |
|---|-------------------------|-------------|------------------|--------------------------------------|
| Forward Voltage at $I_F = 10\text{ mA}$ | V_F | - | 1 | V |
| Leakage Current at $V_R = 20\text{ V}$ at $V_R = 75\text{ V}$ at $V_R = 20\text{ V}, T_j = 150\text{ }^\circ\text{C}$ | I_R I_R I_R | - - - | 25 5 50 | nA μA μA |
| Reverse Breakdown Voltage tested with $100\text{ }\mu\text{A}$ Pulses | $V_{(BR)R}$ | 100 | - | V |
| Capacitance at $V_F = V_R = 0$ | C_{tot} | - | 4 | pF |
| Voltage Rise when Switching ON tested with 50 mA Forward Pulses $t_p = 0.1\text{ s}$, Rise Time $< 30\text{ ns}$, $f_p = 5\text{ to }100\text{ KHz}$ | V_{fr} | - | 2.5 | V |
| Reverse Recovery Time from $I_F = 10\text{ mA}$ to $I_R = 1\text{ mA}$, $V_R = 6\text{ V}$, $R_L = 100\text{ }\Omega$ | t_{rr} | - | 4 | ns |
| Thermal Resistance Junction to Ambient Air | R_{thA} | - | 0.35 ^1 | K/mW |
| Rectification Efficiency at $f = 100\text{ MHz}$, $V_{RF} = 2\text{ V}$ | η_v | 0.45 | - | - |

¹⁾ Valid provided that electrodes are kept at ambient temperature.



Rectification Efficiency Measurement Circuit



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103








ISO 14001:2004
Certificate No. 7116



ISO 9001:2000
Certificate No. 0506098

Dated : 15/09/2007



SEMTECH ELECTRONICS LTD.
 (Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)






ISO/TS 16949 : 2002
 Certificate No. 05103



ISO 14001:2004
 Certificate No. 7116



ISO 9001:2000
 Certificate No. 0506098



SEMTECH ELECTRONICS LTD.
(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 71116



ISO 9001:2000
Certificate No. 0506098