

Caps to Holder FEU, FEU (Med), FAU, FAC



250 VAC · 16 A (UL/CSA)

**Description**

- Fits to type: [FAC](#); [FAU](#); [FEU](#); [FEU \(Med\)](#)

Standards

- IEC 60127-6
- UL 512
- CSA C22.2 no. 39

Approvals

- VDE License Number: 134125
- UL File Number: E39328

References

[General Product Information](#)

Weblinks



[Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Store](#), [Distributor-Stock-Check](#), [Accessories](#), [Product Change Notification \(PCN\)](#)

Technical Data

| | |
|------------------------------|------------------------------|
| Fuse-Link | 5 x 20 or 6.3 x 32 mm |
| Rated Voltage | 250VAC |
| Rated Current | 10A (VDE), 16A (UL/CSA) |
| Degree of Protection | IP 40 |
| Admissible Ambient Air Temp. | -40 °C to 85 °C |
| Material: Cap | Thermoplastic, UL 94V-0 |
| Storage Conditions | 0 °C to 60 °C, max. 70% r.h. |

Abmessungen

31.5 mm



Variants

| Cap | Fuse-Link | Degree of Protection | Order Number |
|-----------|------------|----------------------|--------------|
| Slot Knob | 6.3 x 32mm | IP 40 | 0031.1661 |
| Slot Knob | 5 x 20mm | IP 40 | 0031.1663 |
| Slot Knob | 6.3 x 32mm | IP 40 | 0031.1666 |

Packaging Unit

Plastic Bag (100 pcs.)

Fuseholders

Caps to FEU, FAU, FAC

Caps to Holder FEU, FEU (Med), FAU, FAC



250 VAC · 16A (UL/CSA)



Description

- Fits to type: [FAC](#); [FAU](#); [FEU](#); [FEU \(Med\)](#)

Standards

- IEC 60127-6
- UL 512
- CSA C22.2 no. 39

Approvals

- VDE License Number: 134125
- UL File Number: E39328

References

[General Product Information](#)

Weblinks



[Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

| | |
|------------------------------|------------------------------|
| Fuse-Link | 5 x 20 or 6.3 x 32mm |
| Rated Voltage | 250VAC |
| Rated Current | 10A (VDE), 16A (UL/CSA) |
| Degree of Protection | IP 40 |
| Admissible Ambient Air Temp. | -40 °C to 85 °C |
| Material: Cap | Thermoplastic, UL 94V-0 |
| Storage Conditions | 0 °C to 60 °C, max. 70% r.h. |

Dimensions

Length |-----| 31.5 mm



Variants

[Distributor-Stock-Check](#) | [SCHURTER-Stock-Check](#) | [e-Store](#)

| Cap | Fuse-Link | Degree of Protection | Order Number |
|-----------|------------|----------------------|--------------|
| Slot Knob | 6.3 x 32mm | IP 40 | 0031.1661 |
| Slot Knob | 5 x 20mm | IP 40 | 0031.1663 |
| Slot Knob | 6.3 x 32mm | IP 40 | 0031.1666 |

Packaging Unit

Plastic Bag (100 pcs.)

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments.

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments.