

1X4 RJ45 CONNECTOR MODULE WITH INTEGRATED 10/100 BASE-TX MAGNETICS AND LEDS


P/N: LU4T000-XX

Feature



Example Part Number Format:

X X (Front View)




- RJ-45 connector integrated with X'FMR /impedance resistor/high voltage capacitor
- Size same as RJ-45 connector to save PCB board space.
- Reduce EMI radiation, improve EMI performance.
- Design for 100 BASE transmission over UTP-5 cable.
- Operating temperature range: 0°C to +70°C
- Storage temperature range: -25°C to +85°C .
- Recommended panel

Part Number	Standard LED	Forward*V(Max	(TYP)
3	YELLOW	2.5V	2.1V
4	GREEN	2.5V	2.2V

*With a forward current 20mA


Schematic



1X4 RJ45 CONNECTOR MODULE WITH INTEGRATED 10/100 BASE-TX MAGNETICS AND LEDS

P/N: LU4T000-XX

Mechanical



- 1. Plastic Material : PBT 15% Glass Filled(UL 94V-0), Black Housing.
- 2. Metal Shield : Brass C2680-H, 20u Nickel Plated, t=0.25mm.
- 3. Spring Wire : 0.45mm Dia. Phosphor bronze with 6u gold plated.
- 4. Solder Pin : 0.4x0.4mm, Phosphor bronze with solder Plated.
- 5. Durability : 300 Mating cycles Min.

PCB Layout Mounting Hole(Top View)

