## **New Product Announcement!**

# **High Power Directional Coupler**

ZGDC10-362HP+

50Ω 10dB 380 to 3600 MHz

### **The Big Deal**

High Power Handling: 250W
Low Insertion Loss: 0.11 dB\*

• Rugged IP67 Weatherproof case



Pricing: \$169.95 (QTY 1-9)

#### **Product Overview**

The Mini-Circuits ZGDC10-362HP+ broadband high power directional coupler offers excellent performance across a wide range of popular frequency bands. Built using low loss suspended substrate construction, the ZGDC10-362HP+ can pass up to 3A of DC current from input to output and handle up to 250W CW. The rugged sealed construction makes this coupler ideal for use in field applications or remote monitoring sites; however, it is also ideal for high power lab testing.

#### **Key Features**

| Feature                                     | Advantages                                                                                                                                                                                                 |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Excellent Insertion Loss , 0.11 dB Typ*     | With extremely low insertion loss, this coupler is ideal for critical high power applications.                                                                                                             |
| Ultra High Return Loss, 30 dB Typ           | Outstanding Return loss makes this coupler ideal for sensitive power measurement and other signal distribution applications.                                                                               |
| High Power Handling, 250W                   | Up to 250W CW power handling, combined with low insertion loss and excellent VSWR support operation in high power applications such as transmitters, base stations and high power device characterization. |
| Wide bandwidth                              | Covering 380-3600 MHz, the ZGDC10-362HP+ covers the most popular Cellular, PCS, DCS, WiMAX, and LTE bands.                                                                                                 |
| Excellent Directivity and Coupling Flatness | Typical 28 dB directivity and ±0.6 dB of Coupling flatness provides accurate signal sampling of forward or reflected power.                                                                                |
| Passes DC Current, 3A                       | Capable of passing 3A current, input to output; this coupler is suited for application using remote antenna control or other remote motorized requirements.                                                |
| IP67 Weatherproof Case                      | With an Ingress Protection rating of IP67, the ZGDC10-362HP+ is designed to operate in harsh outdoor applications.                                                                                         |

<sup>\*</sup>Does not include coupling loss



For detailed performance speci & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicipcuits.com