

# Single N-channel MOSFET

ELM14438AA-N

## General description

ELM14438AA-N uses advanced trench technology to provide excellent  $R_{ds(on)}$ , low gate charge and low gate resistance.

## Features

- $V_{ds}=60V$
- $I_d=8.2A$  ( $V_{gs}=10V$ )
- $R_{ds(on)} < 22m\Omega$  ( $V_{gs}=10V$ )
- $R_{ds(on)} < 27m\Omega$  ( $V_{gs}=4.5V$ )

## Maximum absolute ratings


Parameter	Symbol	Limit	Unit	Note	
Drain-source voltage	$V_{ds}$	60	V		
Gate-source voltage	$V_{gs}$	$\pm 20$	V		
Continuous drain current	$I_d$	$T_a=25^\circ C$	8.2	A	1
		$T_a=70^\circ C$	6.6		
Pulsed drain current	$I_{dm}$	40	A	2	
Power dissipation	$P_d$	$T_a=25^\circ C$	3.1	W	
		$T_a=70^\circ C$	2.0		
Junction and storage temperature range	$T_j, T_{stg}$	-55 to 150	$^\circ C$		

## Thermal characteristics

Parameter		Symbol	Typ.	Max.	Unit	Note
Maximum junction-to-ambient	$t \leq 10s$	$R\theta_{ja}$	24	40	$^\circ C/W$	1
Maximum junction-to-ambient	Steady-state		54	75	$^\circ C/W$	
Maximum junction-to-lead	Steady-state	$R\theta_{jl}$	21	30	$^\circ C/W$	3


## Pin configuration

SOP-8 (TOP VIEW)



Pin No.	Pin name
1	SOURCE
2	SOURCE
3	SOURCE
4	GATE
5	DRAIN
6	DRAIN
7	DRAIN
8	DRAIN

## Circuit



# Single N-channel MOSFET

ELM14438AA-N

## Electrical characteristics

T<sub>a</sub>=25°C

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
<b>STATIC PARAMETERS</b>						
Drain-source breakdown voltage	BV <sub>dss</sub>	I <sub>d</sub> =250 μA, V <sub>gs</sub> =0V	60			V
Zero gate voltage drain current	I <sub>dss</sub>	V <sub>ds</sub> =48V			1	μA
		V <sub>gs</sub> =0V		T <sub>j</sub> =55°C	5	
Gate-body leakage current	I <sub>gss</sub>	V <sub>ds</sub> =0V, V <sub>gs</sub> =±20V			100	nA
Gate threshold voltage	V <sub>gs(th)</sub>	V <sub>ds</sub> =V <sub>gs</sub> , I <sub>d</sub> =250 μA	1.0	2.2	3.0	V
On state drain current	I <sub>d(on)</sub>	V <sub>gs</sub> =10V, V <sub>ds</sub> =5V	40			A
Static drain-source on-resistance	R <sub>ds(on)</sub>	V <sub>gs</sub> =10V		16.3	22.0	mΩ
		I <sub>d</sub> =8.2A	T <sub>j</sub> =125°C	30.0	40.0	
		V <sub>gs</sub> =4.5V, I <sub>d</sub> =7.6A		20.0	27.0	mΩ
Forward transconductance	G <sub>fs</sub>	V <sub>ds</sub> =5V, I <sub>d</sub> =8.2A		24		S
Diode forward voltage	V <sub>sd</sub>	I <sub>s</sub> =1A, V <sub>gs</sub> =0V		0.74	1.00	V
Max. body-diode continuous current	I <sub>s</sub>				3	A
<b>DYNAMIC PARAMETERS</b>						
Input capacitance	C <sub>iss</sub>			1920	2300	pF
Output capacitance	C <sub>oss</sub>	V <sub>gs</sub> =0V, V <sub>ds</sub> =30V, f=1MHz		155		pF
Reverse transfer capacitance	C <sub>rss</sub>			116		pF
Gate resistance	R <sub>g</sub>	V <sub>gs</sub> =0V, V <sub>ds</sub> =0V, f=1MHz		0.65	0.80	Ω
<b>SWITCHING PARAMETERS</b>						
Total gate charge (10V)	Q <sub>g</sub>	V <sub>gs</sub> =10V, V <sub>ds</sub> =30V, I <sub>d</sub> =8.2A		47.6	58.0	nC
Total gate charge (4.5V)	Q <sub>g</sub>			24.2	30.0	nC
Gate-source charge	Q <sub>gs</sub>			6.0		nC
Gate-drain charge	Q <sub>gd</sub>			14.4		nC
Turn-on delay time	t <sub>d(on)</sub>			8.2		ns
Turn-on rise time	t <sub>r</sub>	V <sub>gs</sub> =10V, V <sub>ds</sub> =30V		5.5		ns
Turn-off delay time	t <sub>d(off)</sub>	R <sub>l</sub> =3.6 Ω, R <sub>gen</sub> =3 Ω		29.7		ns
Turn-off fall time	t <sub>f</sub>			5.2		ns
Body diode reverse recovery time	t <sub>rr</sub>	I <sub>f</sub> =8.2A, dI/dt=100A/μs		34	41	ns
Body diode reverse recovery charge	Q <sub>rr</sub>	I <sub>f</sub> =8.2A, dI/dt=100A/μs		53		nC

### NOTE :

1. The value of R<sub>θja</sub> is measured with the device mounted on 1in<sup>2</sup> FR-4 board of 2oz. Copper, in still air environment with T<sub>a</sub>=25°C. The value in any given applications depends on the user's specific board design, The current rating is based on the t ≤ 10s thermal resistance rating.
2. Repetitive rating, pulse width limited by junction temperature.
3. The R<sub>θja</sub> is the sum of the thermal impedance from junction to lead R<sub>θjl</sub> and lead to ambient.
4. The static characteristics in Figures 1 to 6 are obtained using 80 μs pulses, duty cycle 0.5%max.
5. These tests are performed with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>a</sub>=25°C. The SOA curve provides a single pulse rating.

# Single N-channel MOSFET

ELM14438AA-N

## Typical electrical and thermal characteristics




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

# Single N-channel MOSFET

ELM14438AA-N




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance