

**EQD020 Series Single Output:
Eighth Brick Through-Hole Power Modules
19 - 60Vdc Input; 3.3Vdc Output; 66W**

RoHS Compliant



Applications

- Distributed power architectures
- Wireless Networks
- Optical and Access Network Equipment
- Enterprise Networks

Options

- Positive logic, Remote On/Off
- Auto restart after fault protection shutdown
- Heat plate
- Case ground pin (with heat plate only)

Description

The EQD020 series DC-DC converters are a new generation of open-frame DC/DC power modules designed to support a 3:1 input voltage range, that allows operation in both 24V or 48V nominal input voltage systems, thus eliminating the need for separate power modules for each input voltage range. These single output DC-DC converters operate over an input voltage range of 19 to 60 Vdc. The series is also designed to provide a tightly regulated output voltage trim range of $\pm 10\% V_{O,Set}$, with output current up to 20A at 3.3Vdc in an industry standard eighth brick package. The output is isolated from the input, allowing versatile polarity configurations and grounding connections. Built in filtering for both input and output minimizes the need for external filtering.

Features

- Compliant to RoHS EU Directive 2002/95/EC (-Z versions)
- Compatible in a Pb-free or SnPb reflow environment (-Z versions)
- High efficiency – 90% at 48Vin, full load
- Industry standard Eighth brick footprint and pin out
57.9 mm x 22.8 mm x 8.5 mm
(2.28 in. x 0.90 in. x 0.335 in.)
- > 3:1 Input voltage range: 19 - 60 Vdc
- Input under/overvoltage protection
- Output overcurrent/voltage protection
- Over-temperature protection
- Tightly regulated output
- Remote sense
- No reverse current during output shutdown
- Negative logic, Remote On/Off
- Output voltage trim $\pm 10\%$
- Wide operating temperature range (-40°C to 85°C)
- *UL** 60950-1 Recognized, *CSA*[†] C22.2 No. 60950-1-03 Certified, and *VDE*[‡] 0805:2001-12 (EN60950-1) Licensed
- *ISO*** 9001 and *ISO* 14001 certified manufacturing facilities
- Licensed for Basic Insulation rating per EN60950-1

* *UL* is a registered trademark of Underwriters Laboratories, Inc.

[†] *CSA* is a registered trademark of Canadian Standards Association.

[‡] *VDE* is a trademark of Verband Deutscher Elektrotechniker e.V.

** *ISO* is a registered trademark of the International Organization of Standards

Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only, functional operation of the device is not implied at these or any other conditions in excess of those given in the operations sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect the device reliability.

Parameter	Device	Symbol	Min	Max	Unit
Input Voltage					
Continuous, Operational	F	V_{IN}	-0.3	60	Vdc
Transient, Operational (10mS minimum)	F	$V_{IN, trans}$		75	Vdc
Transient, Non-operational (100 mS maximum)	F	$V_{IN, trans}$		100	Vdc
Operating Ambient Temperature (see Thermal Considerations section)	F	T_A	-40	85	°C
Storage Temperature	F	T_{stg}	-55	125	°C
I/O Isolation					
Input – Output (100% factory Hi-Pot tested)	F			1500	Vdc

Electrical Specifications

Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions.

Parameter	Device	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	F	V_{IN}	19	24/48	60	Vdc
Maximum Input Current ($V_{IN}=0$ to $V_{IN, max}$, $V_O = V_{o, set}$, $I_O=I_{O, max}$)	F	$I_{IN, max}$			5	Adc
Input Stand-by Current Module on / off disabled ($V_{IN} = V_{IN, nom}$, $V_O = 0$ V)	F	$I_{IN, Stby}$			25	mA
Input No Load Current Module on / off enabled ($V_{IN} = V_{IN, nom}$, $I_O = 0$ A)	F	$I_{IN, NL}$			110	mA
Inrush Transient	F	I^2t			1	A ² s
Input Reflected Ripple Current, peak-to-peak (5Hz to 20MHz, 12µH source impedance; $T_a 25^\circ\text{C}$, $C_{in} = 33\mu\text{F}$)	F				30	mAp-p
Input Ripple Rejection (100 - 120Hz)	F		50			dB

CAUTION: This power module is not internally fused. An input line fuse must always be used.

This power module can be used in a wide variety of applications, ranging from simple standalone operation to being part of a complex power architecture. To preserve maximum flexibility, internal fusing is not included, however, to achieve maximum safety and system protection, always use an input line fuse. The safety agencies require a very fast-acting surface mount fuse with a maximum rating of 6.3 A (see Safety Considerations section). Based on the information provided in this data sheet on inrush energy and maximum dc input current, the same type of fuse with a lower rating can be used. Refer to the fuse manufacturer's data sheet for further information.

Electrical Specifications (continued)

Parameter	Device	Symbol	Min	Typ	Max	Unit
Output Voltage Set-point ($V_{IN} = V_{IN, min} = 24/48$, $I_O = I_{O, max}$, $T_A = 25^\circ\text{C}$)	F	$V_{O, set}$	-1.6		+1.6	% $V_{O, set}$
Output Voltage (Over all line, load, and Temp Conditions until end of life)	F	V_O	-3	-	+3	% V_O
Output Regulation Line ($V_{IN} = V_{IN, min}$ to $V_{IN, max}$)	F		—	0.05	0.4	% $V_{O, nom}$
Load ($I_O = I_{O, min}$ to $I_{O, max}$)	F		—	0.05	0.4	% $V_{O, nom}$
Temperature ($T_{ref} = T_{A, min}$ to $T_{A, max}$)	F		—	0.25	1	% $V_{O, nom}$
Output Ripple and Noise on nominal output ($V_{IN} = V_{IN, nom}$ and $I_O = I_{O, min}$ to $I_{O, max}$, $C_{out} = 1\mu\text{F}$ ceramic // $10\mu\text{F}$ Tantalum capacitor)						
RMS (5Hz to 20MHz bandwidth)	F		—	5	20	mV _{rms}
Peak-to-Peak (5Hz to 20MHz bandwidth)	F		—	50	80	mV _{pk-pk}
External Capacitance ESR ≥ 10 m Ω	F	C_O	0	—	5000	μF
Output Current	F	I_o	0		20	A dc
Output Current Limit Inception (Hiccup Mode) ($V_o = 90\% V_{o, set}$)	F	$I_{o, lim}$	105	115	130	% $I_{o, max}$
Output Short-Circuit Current $V_o \leq 250$ mV @ 25°C	F	$I_{o, s/c}$	—	—	150	% $I_{o, max}$
Efficiency $V_{IN} = 24\text{V}$, $T_A = 25^\circ\text{C}$, $V_o = 3.3\text{V}$, $I_o = I_{O, max}$ A	F	η		90		%
$V_{IN} = 48\text{V}$, $T_A = 25^\circ\text{C}$, $V_o = 3.3\text{V}$, $I_o = I_{O, max}$ A	F	η		90		%
Switching Frequency	F	f_{sw}	150	—	—	KHz
Dynamic Load Response ($dI_o/dt = 1\text{A} / 10\mu\text{s}$; $V_{IN} = V_{IN, nom}$; $T_A = 25^\circ\text{C}$, Output Capacitance = $470\mu\text{F}$ Polymer) Load Change from $I_o = 50\% I_{o, max}$ to $(50\% \pm 25\%) I_{o, max}$ or from $I_o = (50\% \pm 25\%) I_{o, max}$ to $50\% I_{o, max}$						
Peak Deviation	F	V_{pk}	—	3.5	4	% V_o
Settling Time ($V_o < 10\%$ peak deviation)		t_s	—	200	300	μs

Isolation Specifications

Parameter	Min	Typ	Max	Unit
Isolation Capacitance	—	1000	—	pF
Isolation Resistance	10	—	—	M Ω

General Specifications

Parameter	Min	Typ	Max	Unit
Calculated MTBF ($I_o = 0.8 I_{O, max}$, $T_A = 30^\circ\text{C}$) Telcordia SR-332 Issue 1: Method 1 Case 3		2,400,000		Hours
Weight	—	25.3 (0.89)	—	g (oz.)

Feature Specifications

Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions. See Feature Descriptions for additional information.

Parameter	Device	Symbol	Min	Typ	Max	Unit
On/Off Signal interface ($V_{IN}=V_{IN, min}$ to $V_{IN, max}$; Open collector or equivalent, Signal referenced to V_{IN} (-) terminal) Negative Logic: device code suffix "1" Logic Low = module On, Logic High = module Off Positive Logic: No device code suffix required Logic Low = module Off, Logic High = module On						
Logic Low - On/Off Voltage	F	V_{IL}	-0.7	—	1.2	V
Logic Low - Remote On/Off Current	F	I_{IL}	—	—	1.0	mA
Logic High Voltage – (Typ = Open Collector)	F	V_{IH}	—	—	5	V
Logic High maximum allowable leakage current	F	I_{IH}	—	—	50	μ A
External voltage on ON/OFF Pin (to V_{IN} (-) terminal)	F	$V_{ON/OFF}$			13.5	V
Turn-On Delay and Rise Times ($I_O=80\% I_{O, max}$, $T_A = 25^\circ C$) Case 1: On/Off input is set to Logic High and then input power is applied (delay from instant at which $V_{IN} = V_{IN, min}$ until $V_o = 10\%$ of $V_{o, nom}$) Case 2: Input power is applied for at least one second and then the On/Off input is set to logic high (delay from instant at which $V_{on/off} = 0.9V$ until $V_o = 10\%$ of $V_{o, set}$) Output voltage Rise time (time for V_o to rise from 10% of $V_{o, nom}$ to 90% of $V_{o, nom}$)	F	T_{delay}	—	15	30	msec
	F	T_{delay}	—	5	10	msec
	F	T_{rise}	—	20	25	msec
Output voltage overshoot – Startup $I_O = 80\%$ of $I_{O, max}$; $T_A = 25^\circ C$	F			—	1	% $V_{O, set}$
Input Undervoltage Lockout						
Turn-on Threshold	F	V_{UVLO}		18.6	19.0	V
Turn-off Threshold			16.2	16.6		V
Hysteresis			1.5			
Input Overvoltage Lockout						
Turn-on Threshold	F	V_{OVLO}	60	62		V
Turn-off Threshold				64	65	V
Hysteresis				2		
Output Voltage Set point Adjustment						
Output remote sense voltage range (Max voltage drop is 0.33 V)	F	V_{SENSE}			10	% $V_{O, nom}$
Output voltage adjustment range (TRIM)	F	V_{TRIM}	2.97		3.63	Vdc
Over voltage protection	F	$V_{OV, set}$	3.8		4.5	Vdc
Over Temperature Protection						
At $V_{in} = 24V$	F	T_{ref}		125		$^\circ C$
At $V_{in} = 48V$	F	T_{ref}		117		$^\circ C$

Characteristic Curves

The following figures provide typical characteristics for EQD020A at $V_o = 3.3\text{ Vdc}$, $I_o = 20\text{ Adc}$, $T_A = 25^\circ\text{ C}$




Figure 1. Typical Input characteristics.




Figure 4. Typical Output Ripple and Noise at $V_{IN} = 48\text{ V}$.




Figure 2. Typical Converter Efficiency versus Output Current.




Figure 5. Typical Start-Up Characteristics from Remote ON/OFF at $V_{in} = 18\text{ V}$.




Figure 3. Typical Output Ripple and Noise at $V_{IN} = 24\text{ V}$.




Figure 6. Typical Start-Up Characteristics from Remote ON/OFF at $V_{in} = 48\text{ V}$.

Characteristic Curves (continued)

The following figures provide typical characteristics for EQD020A at $V_o = 3.3\text{ Vdc}$, $I_o = 20\text{ A}$, $T_A = 25^\circ\text{ C}$.




Figure 7. Typical Start-Up Characteristics using Input Voltage at $V_{in} = 18\text{ V}$.




Figure 10. Transient Response to a Dynamic Load Change from 75% to 50% of full load at $V_{in} = 24\text{ V}$.




Figure 8. Typical Start-Up Characteristics using Input Voltage at $V_{in} = 48\text{ V}$.




Figure 11. Transient Response to a Dynamic Load Change from 50% to 75% of full load at $V_{in} = 48\text{ V}$.




Figure 9. Transient Response to a Dynamic Load Change from 50% to 75% of full load at $V_{in} = 24\text{ V}$.




Figure 12. Transient Response to a Dynamic Load Change from 75% to 50% of full load at $V_{in} = 48\text{ V}$.

Characteristic Curves (continued)

The following figures provide typical characteristics for EQD020A at $V_o = 3.3$ Vdc.




Figure 13. Thermal Derating Curves for the EQD020 module at 24Vin.




Figure 15. Thermal Derating Curves for the EQD020-H module with heat plate at 48Vin.






Figure 14. Thermal Derating Curves for the EQD020 module at 48Vin.

Test Configurations




NOTE: Measure input reflected ripple current with a simulated source inductance (L_{TEST}) of 12µH. Capacitor C_S offsets possible battery impedance. Measure current as shown above.

Figure 16. Input Reflected Ripple Current Test Setup.



NOTE: All voltage measurements to be taken at the module terminals, as shown above. If sockets are used then Kelvin connections are required at the module terminals to avoid measurement errors due to socket contact resistance.

Figure 17. Output Ripple and Noise Test Setup.



NOTE: All voltage measurements to be taken at the module terminals, as shown above. If sockets are used then Kelvin connections are required at the module terminals to avoid measurement errors due to socket contact resistance.

Figure 18. Output Voltage and Efficiency Test Setup.

Design Considerations

Input Filtering

The power module should be connected to a low ac-impedance source. Highly inductive source impedance can affect the stability of the power module. For the test configuration in Figure 16, a 33µF electrolytic capacitor (ESR<0.1Ω at 100 kHz), mounted close to the power module helps ensure the stability of the unit. Consult your sales representative for further applications guidelines.

Safety Considerations

For safety-agency approval of the system in which the power module is used, the power module must be installed in compliance with the spacing and separation requirements of the end-use safety agency standard, i.e., UL60950-1, CSA C22.2 No. 60950-1-03, EN60950-1 and VDE 0805:2001-12.

These converters have been evaluated to the spacing requirements for Basic Insulation, per the above safety standards; and 1500 Vdc is applied from V_{in} to V_{out} to 100% of outgoing production.

For end products connected to -48V dc nominal DC MAINS (i.e. central office dc battery plant), no further fault testing is required. For all input voltages, other than DC MAINS, where the input voltage is less than 60V dc, if the input meets all of the requirements for SELV, then:

- The output may be considered SELV. Output voltages will remain within SELV limits even with internally-generated non-SELV voltages. Single component failure and fault tests were performed in the power converters.
- One pole of the input and one pole of the output are to be grounded, or both circuits are to be kept floating, to maintain the output voltage to ground voltage within ELV or SELV limits.

The power module has ELV (extra-low voltage) outputs when all inputs are ELV.

All flammable materials used in the manufacturing of these modules are rated 94V-0, or tested to the UL60950 A.2 for reduced thickness.

The input to these units is to be provided with a maximum 6.3 A very fast-acting surface mount fuse in the unearthed lead.

Feature Descriptions

Remote On/Off

The EQD020 series power modules have primary referenced remote On/Off. The remote on/off is open collector compatible with the signal common referenced to the negative input. The standard remote on/off negative logic is such that a unit operates (ON) when the remote on/off signal is low or short circuit to minus V_{IN} . A module will be OFF when the remote on/off pin is open circuit or when the remote on/off signal is high. Observe the maximum external ON/OFF voltage, specified in the Feature Specifications table, when connecting an external source to the ON/OFF pin. The optional positive logic remote on/off is such that a unit operates (ON) when the remote on/off signal is high or open-circuit. A unit will be OFF when the remote on/off signal is low or short-circuited to minus V_{IN} .




Figure 19. Circuit configuration for using Remote On/Off Implementation.

Overcurrent Protection

To provide protection in a fault (output overload) condition, the unit is equipped with internal current-limiting circuitry and can endure current limiting continuously. At the point of current-limit inception, the unit enters a hiccup mode. If the unit is not configured with auto-restart, then it will latch off following the over current condition. The module can be restarted by cycling the dc input power for at least one second or by toggling the remote on/off signal for at least one second. If the unit is configured with the auto-restart option (4), it will remain in the hiccup mode as long as the overcurrent condition exists; it operates normally, once the output current is brought back into its specified range.

Input Under Voltage Lockout

At input voltages below the input under voltage lockout limit, the module operation is disabled. The module will begin to operate at an input voltage above the under voltage lockout turn-on threshold.

Over Temperature Protection

These modules feature an overtemperature protection circuit to safeguard against thermal damage. The circuit shuts down and latches off the module when the maximum device reference temperature is exceeded. The module can be restarted by cycling the dc input power for at least one second or by toggling the remote on/off signal for at least one second. If the auto-restart option (4) is ordered, the module will automatically restart upon cool-down to a safe temperature.

Output Over Voltage Protection

The output over voltage protection scheme of the modules has an independent over voltage loop to prevent single point of failure. This protection feature latches in the event of over voltage across the output. Cycling the on/off pin or input voltage resets the latching protection feature. If the auto-restart option (4) is ordered, the module will automatically restart upon an internally programmed time elapsing.

Remote sense

The EQD020 series power modules have a Remote Sense feature to minimize the effects of distribution losses by regulating the voltage at the Remote Sense pin (See Figure 20). The voltage between the Sense pin and V_O pin must not exceed 0.33V.

The amount of power delivered by the module is defined as the output voltage multiplied by the output current ($V_O \times I_O$). When using Remote Sense, the output voltage of the module can increase, which, if the same output is maintained, increases the power output from the module. Make sure that the maximum output power of the module remains at or below the maximum rated power. When the Remote Sense feature is not being used, connect the Remote Sense pins to the output pins of the module.




Figure 20. Effective Circuit Configuration for remote sense operation.

Feature Descriptions (continued)

Output Voltage Programming

The output voltage is adjustable +10% to -10% of 3.3V. A resistor placed between the Trim pin and Sense (+) increases the output voltage and a resistor

placed between the Trim pin and Sense (-) decreases the output voltage. Figure 21 shows the circuit configuration using an external resistor. The trim resistor should be positioned close to the module. If the trim pin is not used then the pin shall be left open.

The following equations determine the required external resistor value to obtain a percentage output voltage change of Δ%.

To decrease output voltage set point:

$$R_{trim-down} = \left(\frac{510}{\Delta\%} - 10.2 \right) K\Omega$$

Where,

$$\Delta\% = \left| \frac{V_{o,nom} - V_{desired}}{V_{o,nom}} \right| \times 100$$

V_{desired} = Desired output voltage set point (V).

To increase the output voltage set point

$$R_{trim-up} = \left(\frac{5.1 * V_{o,nom} * (100 + \Delta\%)}{1.225 * \Delta\%} - \frac{510}{\Delta\%} - 10.2 \right) K\Omega$$

Although the output voltage can be increased by both the remote sense and by the trim, the maximum increase for the output voltage is not the sum of both. The maximum absolute increase in output voltage, due to simultaneous remote sense and trim increases, shall not exceed the larger of the specified individual remote sense or trim maximum limits shown in the Features Specifications table.




Figure 21. Circuit Configuration to program output voltage using an external resistor.

Pre-Bias Immunity

The modules are able to start into a pre-biased output with a monotonic rise of the output voltage. During shutdown an internal feature implemented in the module ensures there will be no reverse current.

Thermal Considerations

Power modules operate in a variety of thermal environments; however, sufficient cooling should be provided to help ensure reliable operation. Considerations include ambient temperature, airflow, module power dissipation, and the need for increased reliability. A reduction in the operating temperature of the module will result in an increase in reliability. The thermal data is based on physical measurements taken in a wind tunnel. The test set-up is shown in Figure 22.




Figure 22. Thermal Test Set up.

The thermal reference point, T_{ref} , used in the specifications is shown in Figure 23. For reliable operation, this temperature should not exceed the value specified in the Feature Specifications Table.




Figure 23. T_{ref} Temperature Measurement Location.

Through-Hole Lead-Free Soldering Information

The RoHS-compliant through-hole products use the SAC (Sn/Ag/Cu) Pb-free solder and RoHS-compliant components. They are designed to be processed through single or dual wave soldering machines. The pins have an RoHS-compliant finish that is compatible with both Pb and Pb-free wave soldering processes. A maximum preheat rate of 3°C/s is suggested. The wave preheat process should be such that the temperature of the power module board is kept below 210°C. For Pb solder, the recommended pot temperature is 260°C, while the Pb-free solder pot is 270°C max. Not all RoHS-compliant through-hole products can be processed with paste-through-hole Pb or Pb-free reflow process. If additional information is needed, please consult with your Tyco Electronics Power System representative for more details.

Post Solder Cleaning and Drying Considerations


Post solder cleaning is usually the final circuit-board assembly process prior to electrical board testing. The result of inadequate cleaning and drying can affect both the reliability of a power module and the testability of the finished circuit-board assembly. For guidance on appropriate soldering, cleaning and drying procedures, refer to Tyco Electronics *Board Mounted Power Modules: Soldering and Cleaning Application Note (AN04-001)*.

Mechanical Outline

Dimensions are in millimeters and (inches).

Tolerances: x.x mm ± 0.5 mm (x.xx in. ± 0.02 in.) [unless otherwise indicated]

x.xx mm ± 0.25 mm (x.xxx in. ± 0.010 in.)




Mechanical Outline with Heat Plate (-H)

Dimensions are in millimeters and (inches).


Tolerances: x.x mm ± 0.5 mm (x.xx in. ± 0.02 in.) [unless otherwise indicated]

x.xx mm ± 0.25 mm (x.xxx in ± 0.010 in.)


**TOP
VIEW**



**SIDE
VIEW**



**BOTTOM
VIEW**




Recommended Pad Layout

Dimensions are in millimeters and (inches).

Tolerances: x.x mm \pm 0.5 mm (x.xx in. \pm 0.02 in.) [unless otherwise indicated]

x.xx mm \pm 0.25 mm (x.xxx in \pm 0.010 in.)



NOTES:

- 1 FOR 0.031" x 0.025" PIN
USE 0.060" DIA PLATED THROUGH HOLE
- 2 FOR 0.060" DIA PIN
USE 0.076" DIA PLATED THROUGH HOLE
- * CASE GROUND PIN ONLY AVAILABLE WITH
HEAT PLATE

Ordering Information

Please contact your Tyco Electronics' Sales Representative for pricing, availability and optional features.

Table 1. Device Code

Input Voltage	Output Voltage	Output Current	Efficiency	Connector Type	Product Codes	Comcodes
19 – 60V	3.3V	20A	90%	TH	EQD020A0F	CC109103347
19 – 60V	3.3V	20A	90%	TH	EQD020A0F41	CC109104254
19 – 60V	3.3V	20A	90%	TH	EQD020A0F641	CC109113255
19 – 60V	3.3V	20A	90%	TH	EQD020A0FZ	CC109128220
19 – 60V	3.3V	20A	90%	TH	EQD020A0F641Z	CC109122396
19 – 60V	3.3V	20A	90%	TH	EQD020A0F641-HZ	CC109128724

Table 2. Device Options

Option	Suffix
Negative remote on/off logic	1
Auto-restart (from OTP, OVP, OCP)	4
Pin Length: 3.68 mm ± 0.25 mm (0.145 in. ± 0.010 in.)	6
Case ground pin (only available with heat plate, -H)	7
Heat plate	H
RoHS Compliant	Z



World Wide Headquarters
Tyco Electronics Power Systems, Inc.
3000 Skyline Drive, Mesquite, TX 75149, USA
+1-800-526-7819
(Outside U.S.A.: **+1-972-284-2626**)
www.power.tycoelectronics.com
e-mail: techsupport1@tycoelectronics.com

Europe, Middle-East and Africa Headquarters
Tyco Electronics (UK) Ltd
Tel: +44 (0) 1344 469 300

Latin America, Brazil, Caribbean Headquarters
Tyco Electronics Power Systems
Tel: +56 2 209 8211

India Headquarters
Tyco Electronics Systems India Pte. Ltd.
Tel: +91 80 841 1633 x3001

Asia-Pacific Headquarters
Tyco Electronics Singapore Pte. Ltd.
Tel: +65 6416 4283

Tyco Electronics Corporation reserves the right to make changes to the product(s) or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

© 2005 Tyco Electronics Power Systems, Inc., (Mesquite, Texas) All International Rights Reserved.

Document No: DS06-115 ver. 1.1
PDF Name: eqd020_ds.pdf