

Point Source LED

Features:

- Narrow Beam Angle

Applications:

- Optical Switches
- Lineary & Rotary Encoder (Measuring System)




Absolute Maximum Ratings (Ta=25°C)

Items	Symbol	Ratings	Unit
Forward Current (DC)	IF	25	mA
Forward Current (Pulse) ^{*1}	IFP	0.3	A
Reverse Voltage	VR	5	V
Power Dissipation	PD	65	mW
Operating Temperature	T _{opr}	-20 ~ +85	°C
Storage Temperature	T _{stg}	-30 ~ +100	°C
Lead Soldering Temp ^{*2}	T _{sol}	260	°C

*1: Tw=10μS, T=10mS

*2: Time 5 Sec max, Position: Up to 3mm from the body.



Dimensions (Unit:mm)

Electrical & Optical Characteristics (Ta = 25°C)

Items	Symbol	Conditions	Min	Typ	Max	Unit
Power Output	PO	IF=20mA	--	0.7	--	mW
Forward Voltage	VF	IF=20mA	--	2.4	3.0	V
Reverse Current	IR	VR=5V	--	--	100	μA
Peak Wavelength	λ _p	IF=20mA	--	650	--	nm
Spectral Line Half Width	Δλ	IF=20mA	--	25	--	nm
Half Intensity Beam Angle	θ	IF=20mA	--	±5	--	deg.