


Molded, 50 Mil Pitch Resistor Networks




FEATURES

- Lead (Pb)-free available
- 0.090" (2.29 mm) maximum seated height
- Rugged, molded case construction (0.22" wide)
- Highly stable thin film (500 ppm at 70 °C, 10 000 hours)
- Low temperature coefficient, ± 25 ppm/ $^{\circ}$ C (- 55 °C to + 125 °C)
- Wide resistance range 100 Ω to 100 k Ω




Vishay Thin Film offers standard circuits in 16 pin in a medium body molded surface mount package. The networks are available over a resistance range of 100 ohms to 100K ohms. The network features tight ratio tolerances and close TCR tracking. In addition to the standards shown, custom circuits are available upon request.

SCHEMATIC



TYPICAL PERFORMANCE


	ABS	TRACKING
TCR	25	5
	ABS	RATIO
TOL	0.1	0.025



STANDARD ELECTRICAL SPECIFICATIONS			
TEST		SPECIFICATIONS	CONDITION
PIN NUMBER		16	
Resistance Range		100 Ohms to 100K Ohms	
TCR:	Tracking	± 5 ppm/ $^{\circ}$ C	- 55 °C to + 125 °C
	Absolute	± 25 ppm/ $^{\circ}$ C	- 55 °C to + 125 °C
Tolerance:	Ratio	± 0.5 %, ± 0.1 %, ± 0.05 %, ± 0.025 %	+ 25 °C
	Absolute	± 0.1 %, ± 0.5 %, ± 0.25 %, ± 0.1 %	+ 25 °C
Power Rating:	Resistor	Pin 1 Common = 50 mW Isolated = 100 mW	Max. at + 70 °C
	Package	750 mW	Max. at + 70 °C
Stability:	ΔR Absolute	500 ppm	2000 hrs at + 70 °C
	ΔR Ratio	150 ppm	2000 hrs. at + 70 °C
Voltage Coefficient		0.1 ppm/Volt	
Working Voltage		50 Volts	
Operating Temperature Range		- 55 °C to + 125 °C	
Storage Temperature Range		- 55 °C to + 150 °C	
Noise		< - 30 dB	
Thermal EMF		0.08 μ V/ $^{\circ}$ C	
Shelf Life Stability:	Absolute	100 ppm	1 year at + 25 °C
	Ratio	20 ppm	1 year at + 25 °C

* Pb containing terminations are not RoHS compliant, exemptions may apply



DIMENSIONS AND IMPRINTING in inches and millimeters



	INCHES	MM
D	0.050	1.27
E	0.018	0.457
F	0.160	4.06
G	0.08	2.03
H	0.036	0.914
J	0.22	5.59
K	0.244	6.20
L	0.30	7.52
M	0.045	1.14
N	0.003	0.076
P	0.005	1.27
Q	0.008	0.203
R	0.085	2.16
S	0.003	0.076


TYPE	A	B	C
16	0.350" (8.89)	0.400" (10.16)	0.440" (11.176)

DERATING CURVES



GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: **TOMC16031002ZT1** (preferred part number format)



GLOBAL MODEL (4 or 5 digits)	PINS	SCHEMATIC	RESISTANCE	TOLERANCE AND RATIO TOLERANCE	PACKAGING
TOMC (Tin Lead) TOMCT (Lead (Pb)-free) (e3)	16	01 = 15 bussed equal resistors 03 = 7 or 8 Isolated equal resistors	First 3 digits are significant figures and the last digit specifies the number of zeroes to follow. Example: 1002 = 10K 1003 = 100K	Abs. Tol. Ratio ** A = 0.1 % 0.05 % B = 0.1 % 0.1 % C = 0.25 % 0.1 % D = 0.5 % 0.1 % F = 1 % 0.5 % *Z = 0.1 % 0.025 % * Tol. available 1K and up ** Tol. available 250 and up	TAPE AND REEL T0 = 100 Min 100 Mult T1 = 1000 Min 1000 Mult T3 = 300 Min 300 Mult T5 = 500 Min 500 Mult TF = Full Reel 2500 TS = 100 Min 1 Mult UF = TUBED

Historical Part Number example: **TOMC16011002Z** (will continue to be accepted)

TOMC	16	01	1002	Z
SERIES	NUMBER OF LEADS	SCHEMATIC	RESISTANCE	TOLERANCE AND RATIO TOLERANCE



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.