

# EKI-7654C

## 4+2G Combo Port Gigabit Managed Redundant Industrial Ethernet Switch

NEW



### Features

- 2 Gigabit Copper/SFP combo ports, plus 4 Fast Ethernet ports
- Full/half duplex mode flow control
- MDI/MDI-X auto crossover
- SFP socket for Easy and Flexible Fiber Expansion
- Redundancy: Gigabit X-Ring (ultra high-speed recovery time < 10 ms), RSTP/STP (802.1w/1D)
- Management: Web, Telnet, Serial Console, SNMP
- Control: VLAN/GVRP, QoS, IGMP Snooping/ Query, LACP, Rate
- Limit Security: IP/MAC and port binding, DHCP Server, IP access list, 802.1X, SNMPv3 Diagnostic: Port Statistic, Port Mirroring, RMON, SNMP Trap, SMTP, Syslog
- Dual 12 ~ 48 V<sub>DC</sub> power input and 1 relay output

### Introduction

EKI-7654C supports 4 Fast Ethernet ports and 2 Gigabit combo ports. To create reliability in your network, the EKI-7654C comes equipped with a proprietary redundant network protocol – X-Ring that was developed by Advantech, which provides users with an easy way to establish a redundant Ethernet network with ultra high-speed recovery time less than 10 ms. Furthermore, EKI-7654C also supports many advanced network standards to optimize network performance, ease maintenance issues, and secure network safety.

### Specifications

#### Communications

- Standard** IEEE 802.3, 802.3u, 802.3x, 802.3z, 802.1D, 802.1w, 802.1p, 802.1Q, 802.1X, 802.3ad, 802.3ab
- LAN** 100Base-TX, 10/100Base-T, Optional 100Base-FX, 1000Base-SX/LX/LHX/XD/ZX/EZX
- Transmission Distance** Ethernet: Up to 100 m (4-wire Cat.5e, Cat.6 RJ-45 cable suggested for Gigabit port)  
SFP: Up to 110 km (depends on SFP)
- Transmission Speed** Ethernet: 10/100Mbps Auto-Negotiation  
Gigabit Copper: 10/100/1000Mbps, Auto-Negotiation  
Gigabit Fiber: Up to 1000Mbps

#### Interface

- Connectors** 4 x RJ-45 (Ethernet) 2 x RJ-45/SFP (mini-GBIC) combo ports 6-pin removable screw terminal (Power & Relay)
- LED Indicators** System: PWR, PWR1, PWR2, R.M., P-Fail  
10/100T(X): Link/Activity, Duplex/Collision  
Gigabit Copper: Link/Activity, Speed (1000Mbps)  
SFP: Link/Activity
- Console** RS-232 (RJ-45)

#### Network Management

- Configuration** Web browser, Telnet, Serial console, TFTP, SNMPv1/v2c/v3, Port Speed/Duplex Configuration
- VLAN** IEEE 802.1Q, GVRP, Port-based VLAN
- Redundancy** ADVANTECH X-Ring (Recovery time < 10 ms at 50pcs full loading ring structure), Dual Homing, Couple Ring, 802.1w/D RSTP/STP
- Security** IP Access security, port security, DHCP Server, Port and IP Binding, 802.1X Port Access Control
- Traffic Control** IGMP Snooping/Query for multicast group management Port Trunking, Static/802.3ad LACP/Rate limit and storm control IEEE 802.1p QoS CoS/TOS/DSCP priority queuing IEEE 802.3x flow control
- Diagnostics** Port Mirroring, Real-time traffic statistic, MAC Address Table, SNMP, Syslog, E-Mail Alert, SNMP Trap, RMON

#### Mechanism

- Enclosure** IP30, metal shell with solid mounting kits
- Dimensions(W x H x D)** 79 x 152 x 105 mm
- Mounting** DIN-rail, wall

#### Power

- Power Consumption** Max. 10.7 W
- Power Input** 12~ 48 V<sub>DC</sub>, redundant dual inputs
- Fault Output** 1 Relay Output

#### Protection

- ESD (Ethernet)** 4,000 V<sub>DC</sub>
- Surge (EFT for power)** 3,000 V<sub>DC</sub>
- Power Reverse** Present
- Overload** 1.6A @ 12 V<sub>DC</sub> (Re-settable Fuse)

#### Environment

- Operating Temperature** -10 ~ 60° C (14 ~ 140° F)
- Storage Temperature** -40 ~ 85° C (-40 ~ 185° F)
- Operating Humidity** 5 ~ 95% (non-condensing)
- Storage Humidity** 0 ~ 95% (non-condensing)
- MTBF** 284,409 hours

#### Certifications

- Safety** UL 60950-1, CAN/CSA-C22.2 No.60950
- EMC** U.S.A.: FCC Part 15 CISPR 22  
EU: EN55011, EN61000-6-4 EN55022 Class A, EN61000-3-2/3 EN55024  
IEC61000-4-2/3/4/5/6/8, EN61000-6-2/4
- Shock** IEC60068-2-27
- Freefall** IEC60068-2-32
- Vibration** IEC60068-2-6

### Ordering Information

- EKI-7654C** 4+2G Gigabit Managed Ethernet Switch