

# 50.8mm x 50.8mm Precision OCXO



Model: FPC5\_ \_AS Series

Preliminary

Rev. 11/10/2006

Page 1 of 1

[http://www.foxonline.com/need\\_a\\_sample.htm](http://www.foxonline.com/need_a_sample.htm)



## FEATURES

- 5.0V Operation
- Sine Wave Output
- 50.8 x 50.8 x 20.5mm
- SC Cut Resonators

### • PART NUMBER SELECTION [Learn More](#) - Internet Required

Part Number	Model Number	Frequency Stability vs. Temp	Operating Temperature	*Frequency Range (MHz)
690-Frequency-xxxxx	FPC501AS	±2 PPB	0 ~ +50 °C	5.000 ~ 50.000
691-Frequency-xxxxx	FPC502AS	±5 PPB	-20 ~ +70 °C	5.000 ~ 50.000
692-Frequency-xxxxx	FPC503AS	±10 PPB	-40 ~ +75 °C	5.000 ~ 50.000

### • ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	5.000 ~ 50.000 MHz*
Supply Voltage	+5 VDC ± 5%
Power (Warm-Up for 3 minutes)	3 Watts
Power Stabilized at +25°C (Still air)	0.8 Watts Typical
Voltage (± 5% Change)	±2 PPB
Short Term Aging (3 weeks min operation)	± 0.5 PPB / Day
Long Term Aging (After 60 days operation)	± 50 PPB / Year
Allan Variance (1 sec samples)	10 <sup>-11</sup> / Sec
Phase Noise (Offset)	(Typical @ 10 MHz)
10 Hz	-120 dBc
100 Hz	-140 dBc
1 KHz	-155 dBc
10 KHz	-158 dBc
Warm-Up to within ± 100 PPB (Referenced to freq after 1/2 hour power on)	3 minutes
Frequency Adjust (0 to +5 VDC)	± 0.5 PPM Min.
Slope	Positive
Non-Linearity (0.8V-5.0V)	± 10%
Input Impedance	> 100 K
Output	Sine
Output Level into 50 Ohms	> 3 dBm
Harmonics	> 30 dBc
Resonator Type	Coldweld, SC Cut

All specifications subject to change without notice.

\*Specifications are applicable to 10 MHz units. Performance at other frequencies will vary from these values. Other frequencies and performance is available.

Contact Fox Custom Products Center (CPC) for details at 877-369-8041 or email at <http://www.foxonline.com/email.htm>

