



RFMA1216-2W

UPDATED 12/05/2007


12.5 – 15.5 GHz Power Amplifier MMIC

FEATURES

- 12.50– 15.50GHz Operating Frequency Range
- 32 dBm Output Power at 1dB Compression
- 28 dB Typical Power Gain @ 1dB Gain Compression
- -41dBc Typical OIM3 @ each tone Pout 21dBm

APPLICATIONS

- Point-to-point and point-to-multipoint radio
- Military Radar Systems



Caution! ESD sensitive device.

ELECTRICAL CHARACTERISTICS (T_a = 25 °C, 50 ohm, V_{dd}=7V, V_{gg}=-5V)

SYMBOL	PARAMETER/TEST CONDITIONS	MIN	TYP	MAX	UNITS
F	Operating Frequency Range	12.5		15.5	GHz
P1dB	Output Power at 1dB Gain Compression	31	32		dBm
G1dB	Gain @ 1dB gain compression	25	28		dB
OIMD3	Output 3 rd Order Intermodulation Distortion @Δf=10MHz, Each Tone Pout 21 dBm		-41	-38	dBc
Input RL	Input Return Loss		-10	-8	dB
Output RL	Output Return Loss		-15	-8	dB
I _{dd}	Drain Current		1900	2150	mA
V _{dd}	Drain Voltage		7	8	V
V _{gg}	Gate Voltage		-5		V
R _{th}	Thermal Resistance (Au-Sn Eutectic Attach)		4.0	4.5	°C/W
T _b	Operating Base Plate Temperature	-30		+80	°C

MAXIMUM RATINGS @25°C

SYMBOL	CHARACTERISTIC	ABSOLUTE	CONTINUOUS ^{1,2}
V _{DD}	Drain Supply Voltage	12V	8V
V _{GG}	Gate Supply Voltage	-8V	-3V
I _{DD}	Drain Current	I _{dss}	3.6A
I _{GG}	Gate Current	240mA	40mA
P _{IN}	Input Power	20dBm	@ 3dB compression
T _{CH}	Channel Temperature	175°C	150°C
T _{STG}	Storage Temperature	-65/175°C	-65/150°C
P _T	Total Power Dissipation	30.0W	25.2W

1. Operating the device beyond any of the above rating may result in permanent damage.

2. Bias conditions must also satisfy the following equation $V_{dd} \cdot I_{dd} < (T_{CH} - T_b) / R_{TH}$; where T_b = operating base plate temperature

Specifications are subject to change without notice.

Excelics Semiconductor, Inc. 310 De Guigne Drive, Sunnyvale, CA 94085

Phone: 408-737-1711 Fax: 408-737-1868 Web: www.excelics.com

page 1 of 2

Revised December 2007

